

TYTRO® WR 172

New generation high range water-reducing superplasticising admixture for shotcrete

Product Description

TYTRO® WR 172 is the latest technology in the development of high range water-reducing superplasticising admixtures. It is an innovative, versatile, third-generation polycarboxylic ether polymer developed for shotcrete to maximise performance through a wide range of shotcrete strengths.

TYTRO WR 172 contains no added chlorides and complies with AS 1478.1 – 2000 Type HWR. TYTRO WR 172 contains no TEA.

Dispersion

Unlike conventional superplasticisers, which rely on electrostatic repulsion, TYTRO WR 172 has been formulated on carboxylic ether polymers, which are comprised of lateral chains producing superior cement dispersion. Water is absorbed by the polymer, which then allows controlled cement hydration without rapid slump loss or retardation as with conventional naphthalene superplasticisers.

Product Advantages

- TYTRO WR 172 has been developed specifically for shotcrete with a wide range of strengths eliminating the need for other superplasticisers for specific applications.
- It produces very high slump shotcrete at low water cement ratios without segregation and loss of strength.
- It can be added at the batch plant during the batching process eliminating the need for on-site addition.
- It has superior slump retention without retardation.
- Reduction of steam or heat energy curing to achieve high early strengths.
- TYTRO WR 172 is an extremely versatile superplasticiser that has a wide range of applications with superior results.

Application

TYTRO WR 172 allows shotcrete to be produced over a wide range of strengths, at low water-cement ratios with high placement slumps. TYTRO WR 172 can produce high flow shotcrete for tremie and pump mixes that require extended slump life. TYTRO WR 172 is ideal for use in wet mix shotcrete applications to produce high early strengths with reduced heat energy required for curing.

Addition Rates

Addition rates of TYTRO WR 172 can vary depending on the application. However, a typical dose range would be between 400 and 1,200mL / 100kgs total cementitious materials. Higher dose rates can be considered for advanced performance.

For best results TYTRO WR 172 should be added to the mix water during the batching process. At a given water-cement ratio, the slump can be controlled by varying the addition rates. It is GCP's recommendation that trials are conducted beforehand to determine the optimum dose range to suit your application. If further assistance is required please consult your local GCP representative.

Compatibility

TYTRO WR 172 is compatible with Portland cements including fly ash, blast furnace slag silica fume and limestone blends. TYTRO WR 172 can be used with TYTRO RM 475 to produce high quality, water-tolerant shotcretes. It is also compatible with the TYTRO range of shotcrete admixtures. All admixtures should be added to the mix separately and not premixed with other admixtures prior to addition. Please consult your local GCP representative for recommendations on compatible admixtures.

Packaging & Storage

TYTRO WR 172 is available in 1,000L totes and 205L drums.
Shelf life is 12 months.

Health and Safety

See TYTRO WR 172 superplasticiser Material Safety Data Sheet
or consult GCP Applied Technologies.

Dispensing Equipment

Please contact your local GCP representative for further
information regarding the dispensing equipment for this product.

gcpat.com | For technical information: asia.enq@gcpat.com

Australia 1800 855 525 New Zealand +64 9 448 1146 China Mainland +86 21 3158 2888 Hong Kong +852 2675 7898
India: Chennai +91 44 6624 2308 Delhi +91 124 402 8923 Indonesia +62 21 893 4260 Japan +81 3 5226 0231 Korea +82 32 820 0800
Malaysia +60 3 9074 6133 Philippines +63 49 549 7373 Singapore +65 6265 3033 Thailand +66 2 709 4470 Vietnam +84 8 3710 6168


We hope the information here will be helpful. It is based on data and knowledge considered to be true and accurate, and is offered for consideration, investigation and verification by the user, but we do not warrant the results to be obtained. Please read all statements, recommendations, and suggestions in conjunction with our conditions of sale, which apply to all goods supplied by us. No statement, recommendation, or suggestion is intended for any use that would infringe any patent, copyright, or other third party right.

TYTRO is a trademark, which may be registered in the United States and/or other countries, of GCP Applied Technologies, Inc. This trademark list has been compiled using available published information as of the publication date and may not accurately reflect current trademark ownership or status.

© Copyright 2016 GCP Applied Technologies, Inc. All rights reserved.

GCP Applied Technologies Inc., 62 Whittemore Avenue, Cambridge, MA 02140, USA

Printed in Singapore | 03/16 | 200-TYTRO-263



gcp applied technologies