

BITUTHENE[®] Solvent Primer

An ancillary product which contributes to the successful application of waterproofing systems from GCP Applied Technologies

Product Description

BITUTHENE[®] Solvent Primer is a bitumen-based primer in solvent which is specifically formulated to provide good initial adhesion and, more importantly, excellent, permanent adhesion of BITUTHENE[®] Waterproofing Membranes under many kinds of conditions.

Product Uses

BITUTHENE[®] Solvent Primer is used to prime all structural concrete, masonry or wood surfaces on which BITUTHENE[®] Waterproofing Membranes are to be applied. BITUTHENE[®] Solvent Primer is an integral part of the BITUTHENE[®] Waterproofing System. Sufficient primer must be used on the dry surface to condition it to a dust-free state that is suitable for the application of BITUTHENE[®] Waterproofing Membranes.

Application

BITUTHENE[®] Solvent Primer may be applied by spray, roller or brush. Use a heavy nap roller with natural material such as lamb's wool to avoid deterioration.

Apply BITUTHENE[®] Solvent Primer to clean, dry, dust-free and frost-free surfaces at a coverage 6 to 8m² / L. Deep puddles of primer should be avoided as this will lengthen drying time. Rollers or brushes should be dipped into pans to avoid pouring primer directly on the deck and creating puddles.

Allow BITUTHENE[®] Solvent Primer to dry one hour, or until tackfree. On warm days drying may require as little as 30 minutes.

Priming should be limited to what can be covered with BITUTHENE[®] Waterproofing Membrane in a working day. Any areas not covered with membrane during the day must be reprimed. Be sure to cover open pails when not applying primer.

Clean tools with mineral spirits or paint thinner at the end of each day. Rollers can be wrapped tightly overnight in plastic film or release paper from BITUTHENE[®] Waterproofing Membrane. (Mineral spirits and paint thinner are combustible liquids and should be used with care in accordance with the safety instructions of the manufacturer.)

Health and Safety

BITUTHENE[®] Solvent Primer vapour is flammable. Refer to product label and MSDS for handling precautions.

Packaging

BITUTHENE® Solvent Primer is packaged in 20L pails.

Technical Services

For assistance with working drawings for projects and additional technical advice, please contact GCP Applied Technologies.

Release Date: 02/11/18. The information contained in this product data sheet supersedes all previous versions.

gcpat.com.au | For technical information: anz.enq@gcpat.com

Australia 1800 334 444 New Zealand 0800 552 235 China Mainland +86 21 3158 2888 Hong Kong +852 2675 7898 India +91 124 402 8972 Indonesia +62 21 893 4260 Japan +81 3 5226 0231 Korea +82 32 820 0800 Malaysia +60 3 9074 6133
Philippines +63 49 549 7373 Singapore +65 6265 3033 Thailand +66 2 709 4470 Vietnam +84 8 3710 6168

We hope the information here will be helpful. It is based on data and knowledge considered to be true and accurate, and is offered for consideration, investigation and verification by the user, but we do not warrant the results to be obtained. Please read all statements, recommendations, and suggestions in conjunction with our conditions of sale, which apply to all goods supplied by us. No statement, recommendation, or suggestion is intended for any use that would infringe any patent, copyright, or other third party right.

BITUTHENE is a trademark, which may be registered in the United States and/or other countries, of GCP Applied Technologies, Inc. This trademark list has been compiled using available published information as of the publication date and may not accurately reflect current trademark ownership or status.

© Copyright 2019 GCP Applied Technologies, Inc. All rights reserved.

Printed in Australia GCP PDS 056 07/17

GCP Applied Technologies Inc., 2325 Lakeview Parkway, Alpharetta, GA 30009, USA

GCP Australia Pty. Ltd., 14 Colebard Street West, Archerfield, Brisbane, Queensland 4108, Australia

This document is only current as of the last updated date stated below and is valid only for use in Australia. It is important that you always refer to the currently available information at the URL below to provide the most current product information at the time of use. Additional literature such as Contractor Manuals, Technical Bulletins, Detail Drawings and detailing recommendations and other relevant documents are also available on www.gcpat.com.au. Information found on other websites must not be relied upon, as they may not be up-to-date or applicable to the conditions in your location and we do not accept any responsibility for their content. If there are any conflicts or if you need more information, please contact GCP Customer Service.

Last Updated: 2025-05-13

gcpat.com.au/solutions/products/bituthene-solvent-primer