

CHEMFLOOR™ 100

Solvent Free Epoxy Coating

Product Description

CHEMFLOOR™ 100 is a premium quality, multi-purpose, 100% solids, two-pack solventless epoxy system.

Features

CHEMFLOOR™ 100 is suited to a wide variety of applications having the following qualities:

- Food grade AQIS approval & no VOC
- Easy to maintain & dustless
- Multi-Purpose, Seamless & hygienic

CHEMFLOOR™ 100 is a specially formulated low viscosity, two-component epoxy resin system used as a coating or primer to facilitate adhesion of all CHEMFLOOR™ systems to most substrates. It is also used as:

- A chemically resistant, hardwearing clear surface sealer to floors, plant rooms and storage areas.
- A total vapour barrier on concrete floors to prevent moisture vapour damage to timber or sheet vinyl floor finishes.
- A binder used to produce an epoxy mortar made by addition of clean dry aggregates or fillers and used for the repair of defective substrates.

Product Uses

CHEMFLOOR™ 100 epoxy system is ideal for flooring applications to showrooms, basement car-parks, plant rooms, factories, workshops and in pharmaceutical and food processing, water or sewage treatment, etc. It is also used as a multi-purpose binder and surface adhesion promoter.

Preparation

Surfaces must be sound, smooth, and free from dust, oil, grease or other contaminants. Grind or chip off from the concrete surfaces all projections greater than 1.5mm. Remove any loose concrete, then clean and fill holes, cracks and other surface defects with GCP's Super-bond paste or other GCP approved products.

Non-porous, dense concrete should be mechanically abraded.

Concrete should be cured for minimum 28 days and have a moisture content of 5% or less. Moisture testing of concrete prior to installation is recommended

Application

Measure components carefully and mix totally with an electric stirrer. Allow to stand 5 min before use. Preferred mixing and application temp is 15°C–20°C. Apply in two coats by roller or brush. Total coverage should be approximately 0.2–0.3 litres/m².

Packaging

CHEMFLOOR™ 100 is packed, Part A in 20 litre pails and Part B in 10 litre pails.

Typical Properties

PROPERTY	CHEMFLOOR™ 100
Colour	Clear
S.G.	1.1 g/ml
Mix Ratio (volume)	Part A : Part B 2 : 1
Viscosity @ 20°C (mPa.s)	Part A 1400–1800 Part B 50–150
Compressive Strength	85 MPa
Flexural Strength	60 MPa @ 14 days 20°C
Pull Off Strength	> 3 MPa
Pot Life	30 min. @ 20°C (4 litre mix)

Shelf Life

Unopened containers have 12-month shelf life from date of manufacture, when stored in a dry, cool place.

Clean-up

Remove any uncured CHEMFLOOR™ with MULTITEK™ Xylene. Exercise care when using solvents. Please review MSDS before use.

Health and Safety

In case of spills and accidents, refer to the Material Safety Data Sheet (MSDS) of the products or when in doubt contact your local GCP representative. Always wear protective clothing, gloves and protective goggles when handling chemical products. For full information, consult the relevant MSDS.

Limitations

Information contained in this document does not cover all possible application scenarios or imply product suitability for an application. Please contact your local GCP representative or the GCP Technical Department for further information.

Warranties

GCP and contractors recognised by GCP as experienced in the application of GCP products will provide warranties for individual projects. Warranty periods offered are dependent on project details and complexity. Requests for very long warranty periods may necessitate increased membrane thicknesses to ensure longevity. Contact your local GCP representative for further details

Release Date: 02/11/18. The information contained in this product data sheet supersedes all previous versions.

gcpat.com.au | Australia customer service: 1800 334 444 – anzorders@gcpat.com

We hope the information here will be helpful. It is based on data and knowledge considered to be true and accurate, and is offered for consideration, investigation and verification by the user, but we do not warrant the results to be obtained. Please read all statements, recommendations, and suggestions in conjunction with our conditions of sale, which apply to all goods supplied by us. No statement, recommendation, or suggestion is intended for any use that would infringe any patent, copyright, or other third party right.

CHEMFLOOR, and MULTITEK are trademarks of GCP Applied Technologies, Inc. This trademark list has been compiled using available published information as of the publication date and may not accurately reflect current trademark ownership or status.

© Copyright 2019 GCP Applied Technologies, Inc. All rights reserved.

Printed in Australia GCP PDS 032 07/17

GCP Applied Technologies Inc., 2325 Lakeview Parkway, Alpharetta, GA 30009, USA

GCP Australia Pty. Ltd., 14 Colebard Street West, Archerfield, Brisbane, Queensland 4108, Australia

This document is only current as of the last updated date stated below and is valid only for use in Australia. It is important that you always refer to the currently available information at the URL below to provide the most current product information at the time of use. Additional literature such as Contractor Manuals, Technical Bulletins, Detail Drawings and detailing recommendations and other relevant documents are also available on www.gcpat.com.au. Information found on other websites must not be relied upon, as they may not be up-to-date or applicable to the conditions in your location and we do not accept any responsibility for their content. If there are any conflicts or if you need more information, please contact GCP Customer Service.

Last Updated: 2025-06-23

gcpat.com.au/solutions/products/chemfloor-100