

TYTRO[®] RC 430

High performance, rheology-control admixture for shotcrete

Product Description

TYTRO[®] RC 430 is a high performance, liquid rheology-control admixture based on nanometric colloidal silica formulated to improve cohesion, adhesion and early strength development to shotcrete.

Product Advantages

- Reduces or eliminates silica fume
- Improves sprayability
- Reduces rebound losses
- Allows large layer thickness in a single pass
- Low dust in spray applications
- Robust and easy to formulate

Application

TYTRO RC 430 is suitable for all shotcrete applications where high early and final strength, low rebound, and large layer thickness in a single pass are required, and especially in the following applications:

- Temporary and permanent rock support in tunnels
- Rock support in mining
- Slope stabilisation

Health and Safety

Please see TYTRO RC 430 Material Safety Data Sheet or consult GCP Applied Technologies.

Addition Rates

The dosage of TYTRO RC 430 ranges between 0.5% and 2% by weight of cement.

It is GCP's recommendation that trials are conducted beforehand to determine the optimum dose range to suit your application. If further assistance is required, please consult your GCP representative.

Compatibility

TYTRO RC 430 is compatible with all TYTRO admixtures for shotcrete applications. For use with other shotcrete admixture systems, we recommend you to contact GCP Applied Technologies for further advice.

Packaging & Storage

TYTRO RC 430 is available in 1,000L totes and by bulk delivery. Shelf life is 12 months.

Dispensing Equipment

Please contact your local GCP representative for further information regarding the dispensing equipment for this product.

gcpat.com.au | Australia customer service: 1 800 855 525

We hope the information here will be helpful. It is based on data and knowledge considered to be true and accurate, and is offered for consideration, investigation and verification by the user, but we do not warrant the results to be obtained. Please read all statements, recommendations, and suggestions in conjunction with our conditions of sale, which apply to all goods supplied by us. No statement, recommendation, or suggestion is intended for any use that would infringe any patent, copyright, or other third party right.

TYTRO is a trademark, which may be registered in the United States and/or other countries, of GCP Applied Technologies, Inc. This trademark list has been compiled using available published information as of the publication date and may not accurately reflect current trademark ownership or status.

© Copyright 2022 GCP Applied Technologies, Inc. All rights reserved.

GCP Applied Technologies Inc., 2325 Lakeview Parkway, Alpharetta, GA 30009, USA

GCP Australia Pty. Ltd., 14 Colebard Street West, Archerfield, Brisbane, Queensland 4108, Australia

This document is only current as of the last updated date stated below and is valid only for use in Australia. It is important that you always refer to the currently available information at the URL below to provide the most current product information at the time of use. Additional literature such as Contractor Manuals, Technical Bulletins, Detail Drawings and detailing recommendations and other relevant documents are also available on www.gcpat.com.au. Information found on other websites must not be relied upon, as they may not be up-to-date or applicable to the conditions in your location and we do not accept any responsibility for their content. If there are any conflicts or if you need more information, please contact GCP Customer Service.

Last Updated: 2025-05-13

gcpat.com.au/solutions/products/tytro-shotcrete-system/tytro-rc-430