

ZED S94

Anti-Corrosive Metal Primer

Description

ZED S94 is a single-component, anti-corrosive air-drying metal primer. A hand application grade is supplied as standard.

Uses

ZED S94 is used on steel (including galvanised steel) and other metallic surfaces to enhance the bond between GCP's ESSELAC[®] resin based systems and the metal substrate.

Approved for use with the Eliminator bridge deck waterproofing membrane by:

- OTA – ETA No.15/0362, Liquid Applied Bridge Deck Waterproofing, ETAG 033
- British Board of Agreement (UK) – HAPAS Certificates No.11/H169, 11/H170, for Highways England road bridge

Technical Data

PROPERTY	VALUE
Application Temperature Range	-10 to +40 °C
Typical Overcoating Time	
20 °C	30 minutes
10 °C	1 hour
0 °C	3 hour
-10 °C	7.5 hours

Surface Preparation

All surface coating systems are dependent on the quality of surface preparation.

Steel

On steel surfaces all rust, dirt and contamination should be removed to expose bright metal to achieve a surface finish to comply with Swedish standard Sa 2.5. Prior to any blast cleaning the surface must be thoroughly degreased. Amplitude of the surface profile should not exceed 75 microns. Use non-reusable, non-metallic grit.

Mixing

Immediately before use, stir the primer resin thoroughly using a mechanical mixer, such as an air-driven drill (400 – 800 rpm) or intrinsically safe electric drill with mixing paddle.

Application

Application should take place within three hours of grit blasting the substrate. The substrate must be clean and dry. Apply evenly to the substrate by brush or roller.

Do not allow the primer to 'pond' or 'pool'. One application of ZED S94 is usually sufficient. Overcoating with Eliminator or other products is recommended to take place as soon as possible in order to minimise the risk of contamination.

Coverage

Hand Grade – 0.2kg/m²

Cleaning

All tools and equipment should be cleaned with acetone before the material is allowed to cure.

Packaging & Storage

ZED S94 – 5, 20kg and 200kg packs.

All components of the ZED S94 system should be stored in cool, dry, protected conditions, out of direct sunlight and in accordance with the relevant site Health & Safety regulations. Storage temperature must not exceed 25 °C. Do not store near naked flames or foodstuffs.

Stored in unopened containers, under the correct conditions, the components have a minimum shelf life of twelve months. If your product is more than twelve months old you must contact GCP before use.

Health & Safety

Read and understand the product label and Safety Data Sheet (SDS) for each system component. All users should acquaint themselves with this information prior to working with the products and follow the precautionary statements. SDSs can be obtained by contacting your local GCP representative or office.

General Information

ZED S94 is part of a wide range of specialist waterproofing, surfacing and repair materials manufactured and supplied by GCP. If you require any further information on this or any other of our products, please contact our Customer Services Department or visit www.gcpat.com.



gcpat.com.au | Australia customer service: 1800 334 444

We hope the information here will be helpful. It is based on data and knowledge considered to be true and accurate, and is offered for consideration, investigation and verification by the user, but we do not warrant the results to be obtained. Please read all statements, recommendations, and suggestions in conjunction with our conditions of sale, which apply to all goods supplied by us. No statement, recommendation, or suggestion is intended for any use that would infringe any patent, copyright, or other third party right.

ESSELAC is an trademarks, which may be registered in the United States and/or other countries, of GCP Applied Technologies, Inc. This trademark list has been compiled using available published information as of the publication date and may not accurately reflect current trademark ownership or status.

© Copyright 2021 GCP Applied Technologies, Inc. All rights reserved.

GCP Applied Technologies Inc., 62 Whittemore Avenue, Cambridge, MA 02140, USA

GCP Australia Pty. Ltd., 14 Colebard Street West, Archerfield, Brisbane, Queensland 4108, Australia

GCP Applied Technologies Inc., 2325 Lakeview Parkway, Alpharetta, GA 30009, USA

GCP Australia Pty. Ltd., 14 Colebard Street West, Archerfield, Brisbane, Queensland 4108, Australia

This document is only current as of the last updated date stated below and is valid only for use in Australia. It is important that you always refer to the currently available information at the URL below to provide the most current product information at the time of use. Additional literature such as Contractor Manuals, Technical Bulletins, Detail Drawings and detailing recommendations and other relevant documents are also available on www.gcpat.com.au. Information found on other websites must not be relied upon, as they may not be up-to-date or applicable to the conditions in your location and we do not accept any responsibility for their content. If there are any conflicts or if you need more information, please contact GCP Customer Service.

Last Updated: 2025-05-13

gcpat.com.au/solutions/products/eliminator-bridge-deck-waterproofing-solution/zed-s94