

Safety Data Sheet

according to WHS Regulations

Printing Date: 23.09.2022

Version Number: 1.0

Revision Date: 23.09.2022

1 Identification

Product identifier:

Trade name: CHEMFLOOR 100 RESIN CLEAR

Relevant identified uses of the substance or mixture, and uses advised against:

Relevant identified uses of the substance or mixture: Waterproofing.

Identified uses advised against: No further relevant information available.

Details of the supplier of the safety data sheet:

Manufacturer/supplier:

GCP Australia Pty. Ltd. 14 Colebard Street West Archerfield, Queensland 4108 Australia

Further information obtainable from:

Tel: 1800 334 444 Fax: +61 7-3275-7801

APMSDS@gcpat.com

Emergency telephone number: After hours - Tel. No. 1800 039 008

2 Hazard(s) Identification

Classification of the substance or mixture:

Skin Irrit. 2H315 Causes skin irritation.Eye Irritation 2AH319 Causes serious eye irritation.Skin Sens. 1H317 May cause an allergic skin reaction.Muta. 2H341 Suspected of causing genetic defects.

Label elements:

GHS label elements The product is classified and labelled according to the Globally Harmonized System (GHS). **Hazard pictograms**



Signal word Warning

Hazard-determining components of labelling: Epoxy resin 2,3-epoxypropyl o-tolyl ether oxirane, mono[(C12-14-alkyloxy)methyl] derivs

Hazard statements

Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. Suspected of causing genetic defects. **Precautionary statements** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapours/spray. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Page 1/8

Version Number: 1.0

Trade name: CHEMFLOOR 100 RESIN CLEAR

Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
IF ON SKIN: Wash with plenty of water.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
IF exposed or concerned: Get medical advice/attention.
If skin irritation or rash occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
Take off contaminated clothing and wash it before reuse.
Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Information concerning particular hazards for human and environment:

Description of Classification: Classified as hazardous according to the criteria of Safe Work Australia.

Other hazards:

Results of PBT and vPvB assessment:

PBT: Not applicable.

vPvB: Not applicable.

3 Composition and Information on Ingredients

Chemical characterization: Mixture:

Description: Mixture of substances listed below with non-hazardous additions.

Dangerous components:			
25085-99-8	Epoxy resin	50-<100%	
	Skin Irrit. 2, H315; Eye Irritation 2A, H319; Skin Sens. 1, H317		
68609-97-2	oxirane, mono[(C12-14-alkyloxy)methyl] derivs	10-<20%	
	Skin Irrit. 2, H315; Skin Sens. 1, H317		
2210-79-9	2,3-epoxypropyl o-tolyl ether	5-<10%	
	Muta. 2, H341 Skin Irrit. 2, H315; Skin Sens. 1, H317		

Additional information:

Ingredients determined not to be hazardous are present in concentrations that do not exceed the relevant cut-off concentrations as found from NOHSC publication 'List of Designated Hazardous Substances' or have been found NOT to meet the criteria of a hazardous substance as defined in the NOHSC publication 'Approved Criteria for Classifying Hazardous Substances'.

4 First Aid Measures

Description of first aid measures:

General information: Get medical advice/attention if you feel unwell.

After inhalation: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

After skin contact: Wash with plenty of soap and water.

After eye contact: Rinse cautiously with water for several minutes.

After swallowing:

Rinse mouth.

Do NOT induce vomiting.

Information for doctor:

Most important symptoms and effects, both acute and delayed:

May cause sensitisation by skin contact.

Irritating to eyes.

Indication of any immediate medical attention and special treatment needed: No further relevant information available.

ΔU

Revision Date: 23.09.2022

Version Number: 1.0

Trade name: CHEMFLOOR 100 RESIN CLEAR

5 Fire Fighting Measures

Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray.

Special hazards arising from the substance or mixture: No further relevant information available.

Advice for firefighters:

Protective equipment: Wear self-contained respiratory protective device.

Additional information: Collect contaminated fire fighting water separately. It must not enter the sewage system.

6 Accidental Release Measures

Personal precautions, protective equipment and emergency procedures:

Ensure adequate ventilation.

Wear protective equipment. Keep unprotected persons away.

Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system.

Methods and material for containment and cleaning up: Send for recovery or disposal in suitable receptacles.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and Storage

HANDLING

Precautions for safe handling:

Prevent formation of aerosols.

Do not eat, drink or smoke when using this product.

Store in a well-ventilated place. Keep container tightly closed.

Keep only in original container.

Use only outdoors or in a well-ventilated area.

Information about fire - and explosion protection: No special measures required.

Conditions for safe storage, including any incompatibilities:

STORAGE

Information about storage in one common storage facility: Keep respiratory protective device available.

Further information about storage conditions:

Keep container tightly sealed.

Protect from frost.

Store in a dry place.

Keep cool.

Specific end use(s): No further relevant information available.

8 Exposure controls and personal protection

Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 4)

AU

(Contd. of page 2)

Revision Date: 23.09.2022

Version Number: 1.0

Trade name: CHEMFLOOR 100 RESIN CLEAR

Control parameters:

Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

Additional information: Based on the lists valid at the date of SDS creation.

Exposure controls:

PERSONAL PROTECTIVE EQUIPMENT

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Respiratory protection:

Control exposure to ingredients with workplace control parameters if mentioned above. If no ingredients are listed, respiratory protection is generally not required.

If exposure limits are listed and may be exceeded, use approved respiratory protective equipment and filter type appropriate for the listed ingredients. (NIOSH, CEN, etc.).

Protection of hands: Protective gloves.

Material of gloves: Rubber gloves.

Penetration time of glove material:

The exact breakthrough time has to be determined by the manufacturer of the protective gloves and has to be observed.

Eye protection:



Safety glasses with side shield protection.

Body protection:

Use personal protective equipment as required.

Take off contaminated clothing and wash before reuse.

9 Physical and Chemical Properties

Information on basic physical and chemical properties:				
GENERAL INFORMATION Appearance:				
Form:	Liquid. Clear.			
Colour: Odour: Odour threshold:	Characteristic. Not determined.			
pH-value (~):	Not determined.			
Change in conditions:- Melting point/freezing point: Initial boiling point and boiling ran Flash point:	Undetermined. ge: Not determined. 154 °C			
Flammability (solid, gas):	Not applicable.			
Ignition temperature:	Not determined.			
Decomposition temperature: Auto-ignition temperature: Explosive properties:	Not determined. Not determined. Product does not present an explosion hazard.			
EXPLOSION LIMITS Lower:	Not determined.			
	(Contd. on p	page 5) AU		

Revision Date: 23.09.2022

Version Number: 1.0

	(Contd. of page 4
Upper:	Not determined.
Vapour pressure: Density at 20 °C: Vapour density: Evaporation rate:	Not determined. 1.1 g/cm ³ Not determined. Not determined.
Solubility in/Miscibility with:- Water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
VISCOSITY Dynamic: Kinematic: Molecular weight	Not determined. Not determined. Not determined.
Other information:	No further relevant information available.

10 Stability and Reactivity

Reactivity:

Stable under normal conditions. No further relevant information available.

Chemical stability:

Thermal decomposition / conditions to be avoided:

Potentially violent decomposition can occur above 350°C (662°F). Generation of gas during decomposition can cause pressure in closed systems. Pressure build-up can be rapid.

Thermal decomposition / method:

Decomposition products depend upon temperature, air supply and the presence of other materials. Gases are released during decomposition. Uncontrolled exothermic reaction of epoxy resins release phenolics, carbon monoxide, and water.

Possibility of hazardous reactions

No dangerous reactions known.

No further relevant information available.

Conditions to avoid:

Avoid temperatures above 300°C (572°F). Exposure to elevated temperatures can cause product to decompose. Avoid direct sunlight.

Incompatible materials:

Avoid contact with oxidizing materials. Avoid contact with: Acids, Bases. Avoid unintended contact with epoxies.

Hazardous decomposition products: Carbon monoxide and carbon dioxide

Additional information:

HAZARDOUS POLY MERISATION - Will not occur by itself. Masses of more than one pound (0.5 kg) of product plus an aliphatic amine will cause irreversible polymerization with considerable heat build-up.

11 Toxicological Information

Information on toxicological effects:

ACUTE TOXICITY

Primary irritant effect

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/irritation Causes serious eye irritation.

Respiratory or skin sensitisation Sensitisation possible through skin contact.

Additional toxicological information: Suspected of causing genetic defects.

(Contd. on page 6)

Version Number: 1.0

Trade name: CHEMFLOOR 100 RESIN CLEAR

Other information :

The product was classified according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version.

12 Ecological Information

Toxicity:

AQUATIC TOXICITY No further relevant information available.

Persistence and degradability: No further relevant information available.

BEHAVIOUR IN ENVIRONMENTAL SYSTEMS

Bioaccumulative potential: No further relevant information available.

Mobility in soil: No further relevant information available.

ADDITIONAL ECOLOGICAL INFORMATION

General notes: Not known to be hazardous to water.

Results of PBT and vPvB assessment:

PBT: Not applicable. vPvB: Not applicable.

Other adverse effects: No further relevant information available.

13 Disposal considerations

Waste treatment methods:

Recommendation:



Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Refer to State Land Waste Authority for disposal considerations.

UNCLEANED PACKAGING

Recommendation: Disposal must be made according to official regulations.

4 Transport information			
UN-Number ADG, IMDG, IATA	UN3082		
UN proper shipping name ADG, IATA IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy resin, 2,3-epoxypropyl o-tolyl ether) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy resin, 2,3-epoxypropyl o-tolyl ether), MARINE POLLUTANT		
Transport hazard class(es) ADG, IMDG, IATA			
Class Label	9 Miscellaneous dangerous substances and articles. 9		
	(Contd. on pag		

(Contd. of page 5)

Revision Date: 23.09.2022

Version Number: 1.0

Revision Date: 23.09.2022

Trade name: CHEMFLOOR 100 RESIN CLEAR

	(Contd. of page 6)		
Packing group ADG, IMDG, IATA	III		
Environmental hazards: Marine pollutant: Special marking (ADG): Special marking (IATA):	Product contains environmentally hazardous substances: Epoxy resin Symbol (fish and tree) Symbol (fish and tree) Symbol (fish and tree)		
Special precautions for user: Hazard identification number (Kemler code): EMS Number: Stowage Category	Warning: Miscellaneous dangerous substances and articles. 90 F-A,S-F A		
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: Not Regulated			
Transport/Additional information:			
ADG Limited quantities (LQ) Excepted quantities (EQ) Transport category Remarks:	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml 3 ≤5L, ADR Special Provision 375.		
IMDG Limited quantities (LQ) Excepted quantities (EQ) Remarks: IATA	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml ≤5L, IMDG 2.10.2.7		
Remarks:	≤5L, IATA Special Provision 197.		
UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN, 2,3-EPOXYPROPYL O-TOLYL ETHER), 9, III		

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture:

See Section 2 for hazard identification.

Australia: Priority Existing Chemicals

None of the ingredients is listed.

National regulations:

Other regulations, limitations and prohibitive regulations: All ingredients are listed on AICS.

Registered in the international inventory lists: AICS (Australia)

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases:

H315 Causes skin irritation.

- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation. H341 Suspected of causing genetic defects.

(Contd. on page 8)

AU 🗖

Version Number: 1.0

Trade name: CHEMFLOOR 100 RESIN CLEAR

Department issuing SDS:

EHS Department, Asia Pacific Region SCIP, Canlubang, Calamba City, Laguna Philippines 4028 Tel: +63 (02) 8236-6820 to 24

Contact:

The first date of preparation: 05.12.2019

Number of revision times and the latest revision date: 1.0 / 23.09.2022

Revision Date: 23.09.2022

(Contd. of page 7)