



Printing Date: 27.07.2022 Version Number: 1.0 Revision Date: 27.07.2022

1 Identification

Product identifier:

Trade name: CHEMFLOOR FK200 15L KIT PART B

Relevant identified uses of the substance or mixture, and uses advised against:

Relevant identified uses of the substance or mixture: Waterproofing.

Identified uses advised against: No further relevant information available.

Details of the supplier of the safety data sheet:

Manufacturer/supplier:

GCP Australia Pty. Ltd. 14 Colebard Street West Archerfield, Queensland 4108 Australia

Further information obtainable from:

Tel: 1800 334 444 Fax: +61 7-3275-7801 APMSDS@gcpat.com

Emergency telephone number: After hours - Tel. No. 1800 039 008

2 Hazard(s) Identification

Classification of the substance or mixture:

Flam. Liq. 4 H227 Combustible liquid.

Acute Tox. 5 H313 May be harmful in contact with skin.

Acute Tox. 4 H332 Harmful if inhaled.

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Label elements:

GHS label elements The product is classified and labelled according to the Globally Harmonized System (GHS).

Hazard pictograms





GHS05 GHS07

Signal word Danger

Hazard-determining components of labelling:

Isophorondiamine

Benzyl alcohol

Xylene (mixture of isomers)

2,4,6-tris(dimethylaminomethyl)phenol

Reaction product: Bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) oxirane, mono[(C12-14-alkyloxy)methyl] derivs

Hazard statements

Combustible liquid.

May be harmful in contact with skin.

Harmful if inhaled.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

(Contd. on page 2)

(Contd. of page 1)

Safety Data Sheet according to WHS Regulations

Printing Date: 27.07.2022 Version Number: 1.0 Revision Date: 27.07.2022

Trade name: CHEMFLOOR FK200 15L KIT PART B

Precautionary statements

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Do not breathe dusts or mists.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing should not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor.

If skin irritation or rash occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

Wash contaminated clothing before reuse.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information: Exothermic reaction.

Hazard description: Corrosive

Information concerning particular hazards for human and environment:

Description of Classification: Classified as hazardous according to the criteria of Safe Work Australia.

Other hazards:

Results of PBT and vPvB assessment:

PBT: Not applicable. **vPvB:** Not applicable.

3 Composition and Information on Ingredients

Chemical characterization: Mixture:

Description: Mixture of substances listed below with non-hazardous additions.

| Dangerous components: | | | |
|-----------------------|---|---------|--|
| 100-51-6 | Benzyl alcohol | 25-<30% | |
| | Acute Tox. 4, H302; Acute Tox. 4, H332 Acute Tox. 5, H313 | | |
| 2855-13-2 | Isophorondiamine | 25-<30% | |
| | Skin Corr. 1B, H314 Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317 | | |
| 1330-20-7 | Xylene (mixture of isomers) | 10-<20% | |
| | Flam. Liq. 3, H226 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; STOT SE 3, H335 | | |
| 25068-38-6 | Reaction product: Bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) | 10-<20% | |
| | Skin Irrit. 2, H315; Eye Irritation 2A, H319; Skin Sens. 1, H317 | | |
| 90-72-2 | 2,4,6-tris(dimethylaminomethyl)phenol | 5-<10% | |
| | Skin Corr. 1C, H314; Eye Dam. 1, H318 | | |
| 68609-97-2 | oxirane, mono[(C12-14-alkyloxy)methyl] derivs | 5-<10% | |
| | Skin Irrit. 2, H315; Skin Sens. 1, H317 | | |

Additional information:

Ingredients determined not to be hazardous are present in concentrations that do not exceed the relevant cut-off concentrations as found from NOHSC publication 'List of Designated Hazardous Substances' or have been found NOT to meet the criteria of a hazardous substance as defined in the NOHSC publication 'Approved Criteria for Classifying Hazardous Substances'.

Printing Date: 27.07.2022 Version Number: 1.0 Revision Date: 27.07.2022

Trade name: CHEMFLOOR FK200 15L KIT PART B

(Contd. of page 2)

4 First Aid Measures

Description of first aid measures:

General information: Get medical advice/attention if you feel unwell.

After inhalation:

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

IF INHALED: Call a doctor if you feel unwell.

After skin contact: Wash with plenty of soap and water.

After eve contact: Rinse cautiously with water for several minutes.

After swallowing:

Rinse mouth.

Do NOT induce vomiting.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

Information for doctor:

Most important symptoms and effects, both acute and delayed:

Causes burns.

Dizziness

May cause sensitisation by skin contact.

Indication of any immediate medical attention and special treatment needed:

If skin irritation occurs: Get medical advice/attention.

5 Fire Fighting Measures

Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fire with alcohol resistant foam.

For safety reasons unsuitable extinguishing agents: Water jet.

Special hazards arising from the substance or mixture:

During heating or in case of fire poisonous gases are produced.

Formation of toxic gases is possible during heating or in case of fire.

CO, CO2.

Advice for firefighters:

Protective equipment: Wear self-contained respiratory protective device.

Additional information: Collect contaminated fire fighting water separately. It must not enter the sewage system.

6 Accidental Release Measures

Personal precautions, protective equipment and emergency procedures:

Ensure adequate ventilation.

Wear protective equipment. Keep unprotected persons away.

Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system.

Methods and material for containment and cleaning up:

Use neutralising agent.

Send for recovery or disposal in suitable receptacles.

Reference to other sections

See Section 7 for information on safe handling.

(Contd. on page 4)

Printing Date: 27.07.2022 Version Number: 1.0 **Revision Date: 27.07.2022**

Trade name: CHEMFLOOR FK200 15L KIT PART B

(Contd. of page 3)

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and Storage

HANDLING

Precautions for safe handling:

Prevent formation of aerosols.

Do not eat, drink or smoke when using this product.

Store in a well-ventilated place. Keep container tightly closed.

Keep only in original container.

Use only outdoors or in a well-ventilated area.

Information about fire - and explosion protection:

Empty containers may retain hazardous residue, both liquid and vapour. Do not cut, drill, grind or weld on or near container, whether empty or full.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Conditions for safe storage, including any incompatibilities:

STORAGE

Information about storage in one common storage facility: Keep respiratory protective device available.

Further information about storage conditions:

Keep container tightly sealed.

Protect from frost.

Store in a dry place.

Keep cool.

Specific end use(s): No further relevant information available.

Sampling time: post shift Parameter: methyl hippuric acid

8 Exposure controls and personal protection

Additional information about design of technical facilities: No further data; see item 7.

| | Control parameters: | | | | |
|---|---|--|--|--|--|
| | Ingredients with limit values that require monitoring at the workplace: | | | | |
| | 100-51-6 Benzyl alco | 100-51-6 Benzyl alcohol | | | |
| Γ | WEEL (USA) | Long-term value: 10 ppm | | | |
| Γ | 1330-20-7 Xylene (m | nixture of isomers) | | | |
| | | Short-term value: 655 mg/m³, 150 ppm Long-term value: 350 mg/m³, 80 ppm | | | |
| | WEL (Great Britain) | Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV | | | |
| | PEL (USA) | Long-term value: 435 mg/m³, 100 ppm | | | |
| | REL (USA) | Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm | | | |
| | TLV (USA) | Long-term value: 20 ppm BEI, A4 | | | |
| Γ | Ingredients with biological limit values: | | | | |
| Γ | 1330-20-7 Xylene (mixture of isomers) | | | | |
| Γ | BMGV (Great Britain) 650 mmol/mol creatinine | | | | |
| | | Medium: urine | | | |

(Contd. on page 5)

Printing Date: 27.07.2022 Revision Date: 27.07.2022 Version Number: 1.0

Trade name: CHEMFLOOR FK200 15L KIT PART B

BEI (USA) 1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids

Additional information: Based on the lists valid at the date of SDS creation.

Exposure controls:

PERSONAL PROTECTIVE EQUIPMENT

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Respiratory protection:

Control exposure to ingredients with workplace control parameters if mentioned above. If no ingredients are listed, respiratory protection is generally not required.

If exposure limits are listed and may be exceeded, use approved respiratory protective equipment and filter type appropriate for the listed ingredients. (NIOSH, ČEN, etc.).

Protection of hands: Protective gloves.

Material of gloves:

Rubber gloves.

Nitrile rubber.

Penetration time of glove material:

The exact breakthrough time has to be determined by the manufacturer of the protective gloves and has to be observed.

Eye protection:



Safety glasses with side shield protection.

Body protection:

Use personal protective equipment as required.

Take off contaminated clothing and wash before reuse.

9 Physical and Chemical Properties

| Information on basic physical and chemical properties: | | | | |
|--|-------------------------------------|-------------------|--|--|
| GENERAL INFORMATION | | | | |
| Appearance: | | | | |
| Form: | Liquid. | | | |
| Colour: | According to product specification. | | | |
| Odour: | Amine | | | |
| Odour threshold: | Not determined. | | | |
| pH-value (~): | Not determined. | | | |
| Change in conditions:- | | | | |
| Melting point/freezing point: | Undetermined. | | | |
| Initial boiling point and boiling range: Not determined. | | | | |
| Flash point: | >62 °C | | | |
| Flammability (solid, gas): | Not applicable. | | | |
| Ignition temperature: | Not determined. | | | |
| Decomposition temperature: | Not determined. | | | |
| Auto-ignition temperature: | Not determined. | | | |
| Explosive properties: | Not determined. | | | |
| | | Contd. on page 6) | | |

Printing Date: 27.07.2022 Version Number: 1.0 **Revision Date: 27.07.2022**

Trade name: CHEMFLOOR FK200 15L KIT PART B

| | (C | Contd. of pag |
|---|--|---------------|
| EXPLOSION LIMITS | | |
| Lower: | Not determined. | |
| Upper: | Not determined. | |
| Vapour pressure: | Not determined. | |
| Density at 20 °C: | 1 g/cm ³ | |
| Vapour density: | Not determined. | |
| Evaporation rate: | Not determined. | |
| Solubility in/Miscibility with:- | | |
| Water: | Immiscible. | |
| Partition coefficient: n-octanol/water: | Not determined. | |
| VISCOSITY | | |
| Dynamic: | Not determined. | |
| Kinematic: | Not determined. | |
| Molecular weight | Not determined. | |
| Other information: | No further relevant information available. | |

10 Stability and Reactivity

Reactivity:

Stable under normal conditions.

No further relevant information available.

Chemical stability:

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

Possibility of hazardous reactions

No dangerous reactions known.

No further relevant information available.

Conditions to avoid: No further relevant information available.

Incompatible materials: No further relevant information available.

Hazardous decomposition products: Carbon monoxide and carbon dioxide

11 Toxicological Information

Information on toxicological effects:

| ACUTE T | ACUTE TOXICITY | | | | | | |
|------------|--|------------------------------|--|--|--|--|--|
| LD/LC50 | LD/LC50 values relevant for classification: | | | | | | |
| 100-51-6 l | 100-51-6 Benzyl alcohol | | | | | | |
| Oral | LD50 | 1,040 mg/kg (mouse) | | | | | |
| Dermal | LD50 | >2,000 mg/kg (rabbit) | | | | | |
| 2855-13-2 | 2855-13-2 Isophorondiamine | | | | | | |
| Oral | LD50 | 1,030 mg/kg (rat) (OECD 401) | | | | | |
| Dermal | LD50 | mg/kg (rabbit) | | | | | |
| 1330-20-7 | 1330-20-7 Xylene (mixture of isomers) | | | | | | |
| Oral | LD50 | 3,523 mg/kg (rat) | | | | | |
| Inhalative | LC50, 4h | 26 mg/m³ (rat) | | | | | |
| 25068-38- | 25068-38-6 Reaction product: Bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) | | | | | | |
| | LC50, 96h | 220 mg/l (algae) | | | | | |
| | | 3.6 mg/l (bacterial) | | | | | |
| | | 2.4 mg/l (fish) | | | | | |
| | LC50, 48h | 2.8 mg/l (daphnia magna) | | | | | |

(Contd. on page 7)

Printing Date: 27.07.2022 Version Number: 1.0 **Revision Date: 27.07.2022**

Trade name: CHEMFLOOR FK200 15L KIT PART B

90-72-2 2,4,6-tris(dimethylaminomethyl)phenol

LD50 2,169 mg/kg (rat) (OECD 401) Oral

Primary irritant effect

Skin corrosion/irritation

Causes severe skin burns and eye damage. May be harmful in contact with skin.

Serious eye damage/irritation Causes serious eye damage.

Inhalation: Harmful if inhaled.

Respiratory or skin sensitisation Sensitisation possible through skin contact.

Other information:

The product was classified according to the calculation method of the General EU Classification Guidelines for Preparations

as issued in the latest version.

12 Ecological Information

Toxicity:

AQUATIC TOXICITY No further relevant information available.

Persistence and degradability: No further relevant information available.

BEHAVIOUR IN ENVIRONMENTAL SYSTEMS

Bioaccumulative potential: No further relevant information available.

Mobility in soil: No further relevant information available.

ADDITIONAL ECOLOGICAL INFORMATION

General notes: Must not reach sewage water or drainage ditch undiluted or unneutralised.

Results of PBT and vPvB assessment:

PBT: Not applicable. vPvB: Not applicable.

Other adverse effects: No further relevant information available.

13 Disposal considerations

Waste treatment methods:

Recommendation:



Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Refer to State Land Waste Authority for disposal considerations.

UNCLEANED PACKAGING

Recommendation: Disposal must be made according to official regulations.

14 Transport information

UN-Number ADG, IMDG, IATA UN1760

UN proper shipping name ADG, IMDG, IATĀ

CORROSIVE LIQUID, N.O.S. (Isophorondiamine, m-phenylenebis

(methylamine))

(Contd. on page 8)

Printing Date: 27.07.2022 Version Number: 1.0 Revision Date: 27.07.2022

Trade name: CHEMFLOOR FK200 15L KIT PART B

(Contd. of page 7)

Transport hazard class(es)

ADG, IMDG, IATA



Class 8 Corrosive substances.

Label 8

Packing group

ADG, IMDG, IATA

Environmental hazards: Not applicable.

Special precautions for user: Warning: Corrosive substances.

Hazard identification number (Kemler code):

EMS Number:
Segregation groups
Stowage Category
Stowage Code
Sw2 Clear of living quarters.

Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code: Not Regulated

Transport/Additional information:

ADG

Limited quantities (LQ) 5L Excepted quantities (EQ) 5Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

Transport category 3 **Tunnel restriction code** E

IMDG

Limited quantities (LQ) 5L Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture:

See Section 2 for hazard identification.

Australia: Priority Existing Chemicals

None of the ingredients is listed.

National regulations:

Other regulations, limitations and prohibitive regulations: All ingredients are listed on AICS.

Registered in the international inventory lists: AICS (Australia)

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases:

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

(Contd. on page 9)

(Contd. of page 8)

Safety Data Sheet according to WHS Regulations

Printing Date: 27.07.2022 Version Number: 1.0 Revision Date: 27.07.2022

Trade name: CHEMFLOOR FK200 15L KIT PART B

H312 Harmful in contact with skin.

H313 May be harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

Department issuing SDS:

EHS Department, Asia Pacific Region SCIP, Canlubang, Calamba City, Laguna Philippines 4028

Tel: +63 (02) 8236-6820 to 24

Contact:

The first date of preparation: 26.07.2022

Number of revision times and the latest revision date: 1.0 / 27.07.2022

. . . .