



**Printing Date: 29.09.2022** Version Number: 1.0 Revision Date: 29.09.2022

# 1 Identification

#### **Product identifier:**

Trade name: BETEC FLX 120 POWDER

Relevant identified uses of the substance or mixture, and uses advised against:

Relevant identified uses of the substance or mixture: Waterproofing. Identified uses advised against: No further relevant information available.

# Details of the supplier of the safety data sheet:

#### Manufacturer/supplier:

GCP Australia Pty. Ltd. 14 Colebard Street West Archerfield, Queensland 4108 Australia

#### Further information obtainable from:

Tel: 1800 334 444 Fax: +61 7-3275-7801 APMSDS@gcpat.com

Emergency telephone number: After hours - Tel. No. 1800 039 008

#### 2 Hazard(s) Identification

#### Classification of the substance or mixture:

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage.

H350 May cause cancer. Route of exposure: Inhalation.

STOT SE 3 H335 May cause respiratory irritation.

STOT RE 1 H372 Causes damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.

GHS label elements The product is classified and labelled according to the Globally Harmonized System (GHS).

#### Hazard pictograms







GHS05

GHS07

GHS08

#### Signal word Danger

#### Hazard-determining components of labelling:

Portland cement Quartz (SiO2) Calcium oxide

#### **Hazard statements**

Causes skin irritation.

Causes serious eye damage.

May cause cancer. Route of exposure: Inhalation.

May cause respiratory irritation.

Causes damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.

#### **Precautionary statements**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dust/fume/gas/mist/vapours/spray.

(Contd. on page 2)

(Contd. of page 1)

# Safety Data Sheet according to WHS Regulations

**Printing Date: 29.09.2022** Version Number: 1.0 **Revision Date: 29.09.2022** 

#### Trade name: BETEC FLX 120 POWDER

Avoid breathing dust/fume/gas/mist/vapours/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

IF ON SKIN: Wash with plenty of water.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Immediately call a POISON CENTER/doctor.

Get medical advice/attention if you feel unwell.

If skin irritation occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information: Avoid breathing dust

### Information concerning particular hazards for human and environment:

Description of Classification: Classified as hazardous according to the criteria of Safe Work Australia.

Other hazards:

#### Results of PBT and vPvB assessment:

**PBT:** Not applicable. vPvB: Not applicable.

# **3 Composition and Information on Ingredients**

#### **Chemical characterization: Mixture:**

**Description:** Mixture of substances listed below with non-hazardous additions.

•		
Dangerous components:		
14808-60-7 Quartz (SiO2)	Carc. 1A, H350; STOT RE 1, H372	50-<100%
65997-15-1 Portland cement	Eye Dam. 1, H318 Skin Irrit. 2, H315; STOT SE 3, H335	30-<50%
1317-65-3 Limestone		5-<10%
13397-24-5 Gypsum (Ca(SO4).2H2O)		1-<3%
1305-78-8 Calcium oxide	Skin Corr. 1C, H314; Eye Dam. 1, H318 STOT SE 3, H335	1-<3%

#### Additional information:

Ingredients determined not to be hazardous are present in concentrations that do not exceed the relevant cut-off concentrations as found from NOHSC publication 'List of Designated Hazardous Substances' or have been found NOT to meet the criteria of a hazardous substance as defined in the NOHSC publication 'Approved Criteria for Classifying Hazardous Substances'.

### **4 First Aid Measures**

# **Description of first aid measures:**

General information: Get medical advice/attention if you feel unwell.

After inhalation: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Take off immediately all contaminated clothing, and wash immediately with plenty of soap and water.

IF exposed or concerned: Get medical advice/attention.

#### After eve contact:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

(Contd. on page 3)

Printing Date: 29.09.2022 Version Number: 1.0 Revision Date: 29.09.2022

Trade name: BETEC FLX 120 POWDER

(Contd. of page 2)

IF exposed or concerned: Get medical advice/attention.

After swallowing:

Rinse mouth.

Do NOT induce vomiting.

Information for doctor:

Most important symptoms and effects, both acute and delayed: Risk of serious damage to eyes.

Indication of any immediate medical attention and special treatment needed: No further relevant information available.

# **5 Fire Fighting Measures**

Suitable extinguishing agents: CO2, powder.

# Special hazards arising from the substance or mixture:

During heating or in case of fire poisonous gases are produced.

**Advice for firefighters:** 

Protective equipment: Wear self-contained respiratory protective device.

Additional information: Collect contaminated fire fighting water separately. It must not enter the sewage system.

#### **6 Accidental Release Measures**

### Personal precautions, protective equipment and emergency procedures:

Ensure adequate ventilation.

Wear protective equipment. Keep unprotected persons away.

Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system.

Methods and material for containment and cleaning up: Send for recovery or disposal in suitable receptacles.

# Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

# 7 Handling and Storage

#### **HANDLING**

#### Precautions for safe handling:

Do not eat, drink or smoke when using this product.

Store in a well-ventilated place. Keep container tightly closed.

Keep only in original container.

Use only outdoors or in a well-ventilated area.

Information about fire - and explosion protection: No special measures required.

# Conditions for safe storage, including any incompatibilities:

#### **STORAGE**

**Information about storage in one common storage facility:** Keep respiratory protective device available.

## Further information about storage conditions:

Keep container tightly sealed.

Store in a dry place.

(Contd. on page 4)

Printing Date: 29.09.2022 Version Number: 1.0 Revision Date: 29.09.2022

Trade name: BETEC FLX 120 POWDER

(Contd. of page 3)

Keep cool.

**Specific end use(s):** No further relevant information available.

# 8 Exposure controls and personal protection

Additional information about design of technical facilities: No further data; see item 7.

# **Control parameters:**

Control paramet		
Ingredients with lin	nit values that require monitoring at the workplace:	
14808-60-7 Quartz (SiO2)		
WES (Australia)	Long-term value: 0.05 mg/m³ respirable dust	
WEL (Great Britain)	Long-term value: 0.1 mg/m <sup>3</sup>	
PEL (USA)	Long-term value: 0.05* mg/m³ *resp. dust; 30mg/m3/%SiO2+2	
REL (USA)	Long-term value: 0.05* mg/m³ *respirable dust	
TLV (USA)	Long-term value: 0.025* mg/m³ *respirable particulate matter, A2	
65997-15-1 Portland	d cement	
WES (Australia)	Long-term value: 10 mg/m <sup>3</sup>	
WEL (Great Britain)	Long-term value: 10* 4** mg/m³ *inhalable dust **respirable dust	
PEL (USA)	Long-term value: 50 mppcf or 15* 5** mg/m³ *total dust **respirable fraction	
REL (USA)	Long-term value: 10* 5** mg/m³ *total dust **respirable fraction	
TLV (USA)	Long-term value: 1* mg/m³ E; *as respirable fraction, A4	
1317-65-3 Limestone		
TWA (USA)	Short-term value: 10 mg/m³, mg/m3 ppm Long-term value: 10 mg/m³, mg/m3 ppm (Particulate matter no asbestos)	
13397-24-5 Gypsum (Ca(SO4).2H2O)		
REL (USA)	Long-term value: 10* 5** mg/m³ *Total dust; **Respirable fraction	
TLV (USA)	Long-term value: 10* mg/m³ *as inhalable fraction	
1305-78-8 Calcium	1305-78-8 Calcium oxide	
WES (Australia)	Long-term value: 2 mg/m³	
WEL (Great Britain)	Short-term value: 4* mg/m³ Long-term value: 2 1* mg/m³ *respirable fraction	
PEL (USA)	Long-term value: 5 mg/m <sup>3</sup>	
REL (USA)	Long-term value: 2 mg/m <sup>3</sup>	
TLV (USA)	Long-term value: 2 mg/m³	

Additional information: Based on the lists valid at the date of SDS creation.

# **Exposure controls:**

#### PERSONAL PROTECTIVE EQUIPMENT

# General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

### **Respiratory protection:**

Control exposure to ingredients with workplace control parameters if mentioned above. If no ingredients are listed, respiratory protection is generally not required.

**Printing Date: 29.09.2022** Version Number: 1.0 **Revision Date: 29.09.2022** 

Trade name: BETEC FLX 120 POWDER

If exposure limits are listed and may be exceeded, use approved respiratory protective equipment and filter type appropriate for the listed ingredients. (NIOSH, CEN, etc.).

Protection of hands: Protective gloves.

Material of gloves:

Rubber gloves.

Nitrile rubber.

# Penetration time of glove material:

The exact breakthrough time has to be determined by the manufacturer of the protective gloves and has to be observed.

Eye protection: Tightly sealed goggles.

**Body protection:** 

Use personal protective equipment as required.

Take off contaminated clothing and wash before reuse.

9 Physical and Chemical Properties		
Information on basic physical and chemical properties:		
Powder.		
Dark gray.		
Characteristic.		
Not determined.		
Not applicable.		
Undetermined.		
: Not determined.		
Not applicable.		
Not determined.		
Product does not present an explosion hazard.		
Not determined.		
Not determined.		
Not applicable.		
1.3 g/cm <sup>3</sup>		
Not determined.		
Not determined.		
* 111		
Insoluble.		
Not determined.		
Not applicable.		
Not applicable.		
Not determined.		
No further relevant information available.		

Printing Date: 29.09.2022 Version Number: 1.0 Revision Date: 29.09.2022

Trade name: BETEC FLX 120 POWDER

(Contd. of page 5)

# 10 Stability and Reactivity

# **Reactivity:**

Stable under normal conditions.

No further relevant information available.

#### **Chemical stability:**

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

#### Possibility of hazardous reactions

No dangerous reactions known.

No further relevant information available.

Conditions to avoid: No further relevant information available.

**Incompatible materials:** No further relevant information available.

Hazardous decomposition products: Carbon monoxide and carbon dioxide

# 11 Toxicological Information

#### **Information on toxicological effects:**

#### **ACUTE TOXICITY**

Primary irritant effect

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/irritation Causes serious eye damage.

#### Inhalation:

May cause respiratory irritation.

May cause respiratory irritation.

Additional toxicological information: May cause cancer. Route of exposure: Inhalation.

#### Other information:

The product was classified according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version.

# 12 Ecological Information

# **Toxicity:**

AQUATIC TOXICITY No further relevant information available.

Persistence and degradability: No further relevant information available.

#### BEHAVIOUR IN ENVIRONMENTAL SYSTEMS

Bioaccumulative potential: No further relevant information available.

Mobility in soil: No further relevant information available.

# ADDITIONAL ECOLOGICAL INFORMATION

General notes: Must not reach sewage water or drainage ditch undiluted or unneutralised.

# Results of PBT and vPvB assessment:

**PBT:** Not applicable. **vPvB:** Not applicable.

Other adverse effects: No further relevant information available.

Printing Date: 29.09.2022 Version Number: 1.0 Revision Date: 29.09.2022

Trade name: BETEC FLX 120 POWDER

(Contd. of page 6)

# 13 Disposal considerations

#### Waste treatment methods:

#### **Recommendation:**



Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Refer to State Land Waste Authority for disposal considerations.

#### UNCLEANED PACKAGING

**Recommendation:** Disposal must be made according to official regulations.

# 14 Transport information

UN-Number ADG, ADN, IMDG, IATA	Not Regulated	
UN proper shipping name ADG, ADN, IMDG, IATA	Not Regulated	
Transport hazard class(es)		
ADG, ADN, IMDG, IATA Class	Not Regulated	
Packing group ADG, IMDG, IATA	Not Regulated	
Environmental hazards:	Not applicable.	
Special precautions for user:	Not applicable.	
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:  Not Regulated		

#### 15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture:

See Section 2 for hazard identification.

**Australia: Priority Existing Chemicals** 

None of the ingredients is listed.

National regulations:

Other regulations, limitations and prohibitive regulations: All ingredients are listed on AICS.

Registered in the international inventory lists: AICS (Australia)

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

# 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### **Relevant phrases:**

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

(Contd. on page 8)

(Contd. of page 7)

# **Safety Data Sheet** according to WHS Regulations

Printing Date: 29.09.2022 Version Number: 1.0 Revision Date: 29.09.2022

Trade name: BETEC FLX 120 POWDER

H350 May cause cancer.

H372 Causes damage to organs through prolonged or repeated exposure.

## **Department issuing SDS:**

EHS Department, Asia Pacific Region SCIP, Canlubang, Calamba City, Laguna Philippines 4028 Tel: +63 (02) 8236-6820 to 24

# Other Information:

In June 2003, SCOEL, the EU Scientific Committee on Occupational Exposure Limits concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis.

There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis. Therefore preventing the onset of silicosis will also reduce the cancer risk.

#### **Contact:**

The first date of preparation: 26.11.2018

Number of revision times and the latest revision date: 1.0 / 29.09.2022