

Safety Data Sheet
according to WHS Regulations

Printing Date: 22.09.2022

Version Number: 1.0

Revision Date: 22.09.2022

1 Identification**Product identifier:**Trade name: *Bond Coat 3***Relevant identified uses of the substance or mixture, and uses advised against:**

Relevant identified uses of the substance or mixture: Waterproofing.

Identified uses advised against: No further relevant information available.

Details of the supplier of the safety data sheet:**Manufacturer/supplier:**GCP Applied Technologies (UK) Limited
487-488 Ipswich Road,
Slough, Berkshire
SL1 4EP

Tel: +44 (0)1753 490 000

Fax: +44 (0)1753 490 001

De Neef Construction Chemicals BVBA
Industriepark 8,
2220 Heist-op-den-Berg,
Belgium.

Tel: +32 15 24 93 60

Fax: +32 15 24 80 72

GCP Australia Pty. Ltd.
14 Colebard Street West
Archerfield, Queensland 4108
Australiawww.gcpat.comFurther information obtainable from: APMSDS@gcpat.com

Emergency telephone number: After hours - Tel. No. 1800 039 008

2 Hazard(s) Identification**Classification of the substance or mixture:**

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

Label elements:**GHS label elements** The product is classified and labelled according to the Globally Harmonized System (GHS).**Hazard pictograms**

GHS02 GHS07

Signal word Danger

Safety Data Sheet according to WHS Regulations

Printing Date: 22.09.2022

Version Number: 1.0

Revision Date: 22.09.2022

Trade name: *Bond Coat 3*

(Contd. of page 1)

Hazard-determining components of labelling:

Methyl methacrylate
n-butyl methacrylate

Hazard statements

Highly flammable liquid and vapour.
Causes skin irritation.
May cause an allergic skin reaction.
May cause respiratory irritation.

Precautionary statements

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Ground and bond container and receiving equipment.
Use explosion-proof [electrical/ventilating/lighting] equipment.
Use non-sparking tools.
Take action to prevent static discharges.
Avoid breathing dust/fume/gas/mist/vapours/spray.
Wash thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Contaminated work clothing should not be allowed out of the workplace.
Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
Call a POISON CENTER/doctor if you feel unwell.
If skin irritation or rash occurs: Get medical advice/attention.
Take off contaminated clothing and wash it before reuse.
In case of fire: Use CO₂, powder or water spray to extinguish.
Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard description: Flammable**Other hazards:****Results of PBT and vPvB assessment:**

PBT: Not applicable.
vPvB: Not applicable.

3 Composition and Information on Ingredients

Chemical characterization: Mixture:**Description:** Mixture of substances listed below with non-hazardous additions.**Dangerous components:**

80-62-6	Methyl methacrylate	30-<50%
	Flam. Liq. 2, H225 Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	
97-88-1	n-butyl methacrylate	5-<10%
	Flam. Liq. 3, H226 Skin Irrit. 2, H315; Eye Irritation 2A, H319; Skin Sens. 1, H317; STOT SE 3, H335	
99-97-8	N,N-dimethyl-p-toluidine	0.1-<1%
	Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331	
	Carc. 2, H351; STOT RE 2, H373 Flam. Liq. 4, H227	

Additional information:

Ingredients determined not to be hazardous are present in concentrations that do not exceed the relevant cut-off concentrations as found from NOHSC publication 'List of Designated Hazardous Substances' or have been found NOT to meet the criteria of a hazardous substance as defined in the NOHSC publication 'Approved Criteria for Classifying Hazardous Substances'.

(Contd. on page 3)

Safety Data Sheet
according to WHS Regulations

Printing Date: 22.09.2022

Version Number: 1.0

Revision Date: 22.09.2022

Trade name: *Bond Coat 3*

(Contd. of page 2)

4 First Aid Measures

Description of first aid measures:

General information: Get medical advice/attention if you feel unwell.

After inhalation: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

After skin contact: Wash with plenty of soap and water.

After eye contact: Rinse cautiously with water for several minutes.

After swallowing:

Rinse mouth.

Do NOT induce vomiting.

Information for doctor:

Most important symptoms and effects, both acute and delayed: May cause sensitisation by skin contact.

Indication of any immediate medical attention and special treatment needed: No further relevant information available.

5 Fire Fighting Measures

Suitable extinguishing agents:

CO₂, extinguishing powder or water spray. Fight larger fire with alcohol resistant foam.

For safety reasons unsuitable extinguishing agents: Water jet.

Special hazards arising from the substance or mixture: No further relevant information available.

Advice for firefighters:

Protective equipment: Wear self-contained respiratory protective device.

Additional information: Collect contaminated fire fighting water separately. It must not enter the sewage system.

6 Accidental Release Measures

Personal precautions, protective equipment and emergency procedures:

Ensure adequate ventilation.

Wear protective equipment. Keep unprotected persons away.

Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system.

Methods and material for containment and cleaning up: Send for recovery or disposal in suitable receptacles.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and Storage

HANDLING

Precautions for safe handling:

Prevent formation of aerosols.

Flammable mixtures with air can be formed in emptied containers. Do not puncture, cut, drill, heat or weld uncleaned drums.

Do not eat, drink or smoke when using this product.

Store in a well-ventilated place. Keep container tightly closed.

Keep only in original container.

(Contd. on page 4)

Safety Data Sheet

according to WHS Regulations

Printing Date: 22.09.2022

Version Number: 1.0

Revision Date: 22.09.2022

Trade name: *Bond Coat 3*

(Contd. of page 3)

Use only outdoors or in a well-ventilated area.

Information about fire - and explosion protection:


Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Use explosion-proof apparatus / fittings and spark-proof tools.

Empty containers may retain hazardous residue, both liquid and vapour. Do not cut, drill, grind or weld on or near container, whether empty or full.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Ground/bond container and receiving equipment.

Conditions for safe storage, including any incompatibilities:
STORAGE

Requirements to be met by storerooms and receptacles: Store in a cool location.

Further information about storage conditions:

Keep container tightly sealed.

Protect from frost.

Store in a dry place.

Keep cool.

Specific end use(s): No further relevant information available.

8 Exposure controls and personal protection

Additional information about design of technical facilities: No further data; see item 7.

Control parameters:
Ingredients with limit values that require monitoring at the workplace:
80-62-6 Methyl methacrylate

WES (Australia)	Short-term value: 416 mg/m ³ , 100 ppm Long-term value: 208 mg/m ³ , 50 ppm Sen
WEL (Great Britain)	Short-term value: 416 mg/m ³ , 100 ppm Long-term value: 208 mg/m ³ , 50 ppm
PEL (USA)	Long-term value: 410 mg/m ³ , 100 ppm
REL (USA)	Long-term value: 410 mg/m ³ , 100 ppm
TLV (USA)	Short-term value: 100 ppm Long-term value: 50 ppm DSEN, A4

99-97-8 N,N-dimethyl-p-toluidine

WEEL (USA)	Long-term value: 0.5 ppm
------------	--------------------------

Additional information: Based on the lists valid at the date of SDS creation.

Exposure controls:
PERSONAL PROTECTIVE EQUIPMENT
General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Respiratory protection:

Control exposure to ingredients with workplace control parameters if mentioned above. If no ingredients are listed, respiratory protection is generally not required.

If exposure limits are listed and may be exceeded, use approved respiratory protective equipment and filter type appropriate

(Contd. on page 5)

Safety Data Sheet

according to WHS Regulations

Printing Date: 22.09.2022

Version Number: 1.0

Revision Date: 22.09.2022

Trade name: *Bond Coat 3*

(Contd. of page 4)

for the listed ingredients. (NIOSH, CEN, etc.).

Protection of hands: Protective gloves.

Material of gloves: Rubber gloves.

Penetration time of glove material:

The exact breakthrough time has to be determined by the manufacturer of the protective gloves and has to be observed.

Eye protection:



Safety glasses with side shield protection.

Body protection:

Use personal protective equipment as required.

Take off contaminated clothing and wash before reuse.

9 Physical and Chemical Properties

Information on basic physical and chemical properties:

GENERAL INFORMATION

Appearance:

Form:	Liquid.
Colour:	Red.
Odour:	Characteristic.
Odour threshold:	Not determined.

pH-value (~): Not determined.

Change in conditions:-

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	100 °C
Flash point:	16 °C

Flammability (solid, gas): Highly flammable.

Ignition temperature: Not determined.

Decomposition temperature: Not determined.

Auto-ignition temperature: Not determined.

Explosive properties: In use, may form flammable/explosive vapour-air mixture.

EXPLOSION LIMITS

Lower:	Not determined.
Upper:	Not determined.

Vapour pressure: Not determined.

Density: Not determined.

Relative density: ~1.1

Vapour density: Not determined.

Evaporation rate: Not determined.

Solubility in/Miscibility with:-

Water: Not miscible or difficult to mix.

Partition coefficient: n-octanol/water: Not determined.

VISCOSITY

Dynamic at 20 °C: 300 mPas

Kinematic: Not determined.

Molecular weight: Not determined.

Other information: No further relevant information available.

AU
(Contd. on page 6)

Safety Data Sheet
according to WHS Regulations

Printing Date: 22.09.2022

Version Number: 1.0

Revision Date: 22.09.2022

Trade name: *Bond Coat 3*

(Contd. of page 5)

10 Stability and Reactivity

Reactivity: Will exothermically polymerise in the presence of initiators.

Chemical stability: Stable in the presence of inhibitor.

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

Possibility of hazardous reactions

Susceptible to polymerisation initiated by prolonged storage or the presence of catalyst.

Conditions to avoid: Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Incompatible materials:

Polymerisation catalysts, such as peroxy or azo compounds, strong acids, alkalis and oxidising agents. Oxides and salts of transition metals. Organic Nitrogen containing compounds. Cyclohexanone/Cyclohexenol tautomer.

Hazardous decomposition products: Carbon monoxide and carbon dioxide

11 Toxicological Information

Information on toxicological effects:

ACUTE TOXICITY

LD/LC50 values relevant for classification:

97-88-1 n-butyl methacrylate

Dermal	LD50	22,600 mg/kg (rat)
	LD50	11,300 mg/kg (rabbit)
Inhalative	LC50, 4h	4,910 mg/l (rat)

Primary irritant effect

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/irritation No irritating effect.

Inhalation: May cause respiratory irritation.

Respiratory or skin sensitisation Sensitisation possible through skin contact.

Other information :

The product was classified according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version.

12 Ecological Information

Toxicity:

AQUATIC TOXICITY No further relevant information available.

Persistence and degradability: No further relevant information available.

BEHAVIOUR IN ENVIRONMENTAL SYSTEMS

Bioaccumulative potential: No further relevant information available.

Mobility in soil: No further relevant information available.

ADDITIONAL ECOLOGICAL INFORMATION

General notes: Not known to be hazardous to water.

Results of PBT and vPvB assessment:

PBT: Not applicable.

vPvB: Not applicable.

Other adverse effects: No further relevant information available.

.AU
(Contd. on page 7)

Safety Data Sheet according to WHS Regulations

Printing Date: 22.09.2022

Version Number: 1.0

Revision Date: 22.09.2022

Trade name: *Bond Coat 3*

(Contd. of page 6)

13 Disposal considerations

Waste treatment methods:
Recommendation:



Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Refer to State Land Waste Authority for disposal considerations.

UNCLEANED PACKAGING

Recommendation: Disposal must be made according to official regulations.

14 Transport information

UN-Number ADG, IMDG, IATA	UN1866
UN proper shipping name ADG, IMDG, IATA	RESIN SOLUTION
Transport hazard class(es) ADG, IMDG, IATA	
	
Class Label	3 Flammable liquids. 3
Packing group ADG, IMDG, IATA	III
Environmental hazards:	Not applicable.
Special precautions for user:	Warning: Flammable liquids.
Hazard identification number (Kemler code):	-
EMS Number:	F-E, <u>S</u> -E
Stowage Category	A
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:	Not Regulated
Transport/Additional information:	
ADG Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
Transport category Tunnel restriction code	3 E
IMDG Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

 AU
(Contd. on page 8)

Safety Data Sheet
according to WHS Regulations

Printing Date: 22.09.2022

Version Number: 1.0

Revision Date: 22.09.2022

Trade name: *Bond Coat 3*

(Contd. of page 7)

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture:

See Section 2 for hazard identification.

Australia: Priority Existing Chemicals

None of the ingredients is listed.

National regulations:

Other regulations, limitations and prohibitive regulations: All ingredients are listed on AICS.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases:

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H227 Combustible liquid.

H301 Toxic if swallowed.

H311 Toxic in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

Department issuing SDS:

EHS Department,

Asia Pacific Region

SCIP, Canlubang, Calamba City, Laguna

Philippines 4028

Tel: +63 (02) 8236-6820 to 24

Contact:

The first date of preparation: 01.03.2021

Number of revision times and the latest revision date: 1.0 / 22.09.2022

AU