

Safety Data Sheet

according to WHS Regulations

Printing Date: 01.12.2022

Version Number: 1.0

Revision Date: 19.10.2022

1 Identification

Product identifier:

Trade name: Silcor 780 HI-LP (Isocyanate)

Relevant identified uses of the substance or mixture, and uses advised against:

Relevant identified uses of the substance or mixture: Waterproofing.

Identified uses advised against: No further relevant information available.

Details of the supplier of the safety data sheet:

Manufacturer/supplier:

GCP Australia Pty. Ltd. 14 Colebard Street West Archerfield, Queensland 4108 Australia

Further information obtainable from:

Tel: 1800 334 444 Fax: +61 7-3275-7801

APMSDS@gcpat.com

Emergency telephone number: After hours - Tel. No. 1800 039 008

2 Hazard(s) Identification

Classification of the substance or mixture:

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irritation 2A H319 Causes serious eye irritation.

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Carc. 2 H351 Suspected of causing cancer.

STOT SE 3 H335 May cause respiratory irritation.

STOT RE 1 H372 Causes damage to organs through prolonged or repeated exposure.

Label elements:

GHS label elements The product is classified and labelled according to the Globally Harmonized System (GHS).

Hazard pictograms



Signal word Danger

Hazard-determining components of labelling:

MDI Polyurethane Prepolymer Diphenylmethane-4,4'-di-isocyanate

Hazard statements

Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. Suspected of causing cancer.

Version Number: 1.0

| | (Contd. of page 1) |
|--|--------------------|
| May cause respiratory irritation. | (Conta. of page 1) |
| Causes damage to organs through prolonged or repeated exposure. | |
| Precautionary statements | |
| Obtain special instructions before use. | |
| Do not handle until all safety precautions have been read and understood. | |
| Do not breathe dust/fume/gas/mist/vapours/spray. | |
| Avoid breathing dust/fume/gas/mist/vapours/spray. | |
| Wash thoroughly after handling. | |
| Do not eat, drink or smoke when using this product. | |
| Use only outdoors or in a well-ventilated area. | |
| Contaminated work clothing should not be allowed out of the workplace. | |
| Wear protective gloves/protective clothing/eye protection/face protection. | |
| Wear respiratory protection. | |
| IF ON SKIN: Wash with plenty of water. | |
| IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. | |
| IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. C | Continue |
| rinsing. | |
| IF exposed or concerned: Get medical advice/attention. | |
| Call a POISON CENTER/doctor if you feel unwell. | |
| Get medical advice/attention if you feel unwell. | |
| If skin irritation or rash occurs: Get medical advice/attention. | |
| If eye irritation persists: Get medical advice/attention. | |
| If experiencing respiratory symptoms: Call a POISON CENTER/doctor. | |
| Take off contaminated clothing and wash it before reuse. | |
| Store in a well-ventilated place. Keep container tightly closed. | |
| Store locked up. | |
| Dispose of contents/container in accordance with local/regional/national/international regulations. | |
| Other hazards: | |
| | |

Results of PBT and vPvB assessment:

PBT: Not applicable. vPvB: Not applicable.

3 Composition and Information on Ingredients

Chemical characterization: Mixture:

Description: Mixture of substances listed below with non-hazardous additions.

| Dangerous components: | | | | |
|-----------------------|--|---------|--|--|
| 101-68-8 | Diphenylmethane-4,4'-di-isocyanate | 30-<50% | | |
| | Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 1, H372 Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irritation 2A, H319; Skin Sens. 1, H317; STOT SE 3, H335 | | | |
| 108-32-7 | Propylene carbonate | 10-<20% | | |
| | Eye Irritation 2A, H319 | | | |

Additional information:

Ingredients determined not to be hazardous are present in concentrations that do not exceed the relevant cut-off concentrations as found from NOHSC publication 'List of Designated Hazardous Substances' or have been found NOT to meet the criteria of a hazardous substance as defined in the NOHSC publication 'Approved Criteria for Classifying Hazardous Substances'.

4 First Aid Measures

Description of first aid measures:

General information: Get medical advice/attention if you feel unwell.

After inhalation:

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

IF INHALED: Call a doctor if you feel unwell.

After skin contact: Wash with plenty of soap and water.

(Contd. on page 3)

Revision Date: 19.10.2022

Version Number: 1.0

Trade name: Silcor 780 HI-LP (Isocyanate)

After eye contact: Rinse cautiously with water for several minutes. After swallowing: Rinse mouth. Do NOT induce vomiting. Call for a doctor immediately. Information for doctor: Most important symptoms and effects, both acute and delayed: May cause sensitisation by skin contact. Irritating to eyes. Indication of any immediate medical attention and special treatment needed: No further relevant information available.

5 Fire Fighting Measures

Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray.

Special hazards arising from the substance or mixture: During heating or in case of fire poisonous gases are produced.

Advice for firefighters:

Protective equipment: Wear self-contained respiratory protective device.

Additional information: Collect contaminated fire fighting water separately. It must not enter the sewage system.

6 Accidental Release Measures

Personal precautions, protective equipment and emergency procedures:

Ensure adequate ventilation.

Wear protective equipment. Keep unprotected persons away.

Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system.

Methods and material for containment and cleaning up: Send for recovery or disposal in suitable receptacles.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and Storage

HANDLING

Precautions for safe handling:

Prevent formation of aerosols.

Do not eat, drink or smoke when using this product.

Store in a well-ventilated place. Keep container tightly closed.

Keep only in original container.

Use only outdoors or in a well-ventilated area.

Information about fire - and explosion protection: No special measures required.

Conditions for safe storage, including any incompatibilities:

STORAGE

Information about storage in one common storage facility: Keep respiratory protective device available.

Revision Date: 19.10.2022

(Contd. of page 2)

Version Number: 1.0

Trade name: Silcor 780 HI-LP (Isocyanate)

Revision Date: 19.10.2022

(Contd. of page 3)

Further information about storage conditions:

Keep container tightly sealed.

Protect from frost.

Store in a dry place.

Keep cool.

Specific end use(s): No further relevant information available.

8 Exposure controls and personal protection

Additional information about design of technical facilities: No further data; see item 7.

Control parameters:

| Control parameters. | | | | |
|---|--|--|--|--|
| Ingredients with limit values that require monitoring at the workplace: | | | | |
| 101-68-8 Diphenylmethane-4,4'-di-isocyanate | | | | |
| Short-term value: 0.07 mg/m ³ Long-term value: 0.02 mg/m ³ Sen; as -NCO | | | | |
| Short-term value: 0.07 mg/m ³ Long-term value: 0.02 mg/m ³ Sen; as -NCO | | | | |
| EL (USA) Peak limitation: 0.2 mg/m ³ , 0.02 ppm | | | | |
| Long-term value: 0.05 mg/m ³ , 0.005 ppm Peak limitation: 0.2* mg/m ³ , 0.02* ppm *10-min | | | | |
| Long-term value: 0.051 mg/m ³ , 0.005 ppm | | | | |
| Ingredients with biological limit values: | | | | |
| ethane-4,4'-di-isocyanate | | | | |
| BMGV (Great Britain) 1 µmol creatinine/mol | | | | |
| Medium: urine | | | | |
| Sampling time: At the end of the period od exposure | | | | |
| Parameter: isocyanate-derived diamine | | | | |
| | | | | |

Additional information: Based on the lists valid at the date of SDS creation.

Exposure controls:

Appropriate engineering controls Local exhaust ventilation is recommended.

PERSONAL PROTECTIVE EQUIPMENT

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Respiratory protection:

Isocyanates (contained in this part and when mixed) are known as respiratory sensitisers.

Atmospheric levels should be maintained below the occupational exposure limits. When atmospheric levels exceed those limits or are unknown, respiratory protection is required.

For spray applications in well ventilated areas, use an approved full-face air purifying respirator or a powered air purifying respirator equipped with an organic vapor sorbent filter (EU Type A, NIOSH Black, etc.) and particulate pre-filter (EU Type P2 or P3, NIOSH N95 or better, etc.). A supplied air respirator may also be used and is often the preferred option.

Where spray application in poorly ventilated areas is unavoidable, a supplied air respirator should be used.

For hand applications, unless monitoring data confirms that respiratory protection is not necessary, use an approved half-face air purifying respirator equipped with an organic vapor sorbent filter (EU Type A, NIOSH Black, etc.) and particulate pre-filter (EU Type P2, NIOSH N95, etc.).

For emergency response, an approved positive pressure Self Contained Breathing Apparatus (SCBA) or positive pressure air line with auxiliary self-contained air supply is recommended.

Protection of hands: Protective gloves.

Safety Data Sheet according to WHS Regulations

Printing Date: 01.12.2022

Version Number: 1.0

K

Trade name: Silcor 780 HI-LP (Isocyanate)

Material of gloves: Rubber gloves.

Penetration time of glove material:

The exact breakthrough time has to be determined by the manufacturer of the protective gloves and has to be observed.

Eye protection:



A face shield should also be worn if there is potential exposure to splash or spray.

Protective goggles.

Body protection:

Protective work clothing.

Take off contaminated clothing and wash before reuse.

9 Physical and Chemical Properties

| Information on basic physical and chemical properties: | | |
|--|---|--|
| GENERAL INFORMATION Appearance: Form: Colour: Odour: Odour: Odour threshold: | Liquid. Transparent. Slight Musty Not determined. | |
| pH-value (~): | Not determined. | |
| Change in conditions:- Melting point/freezing point: Initial boiling point and boiling range Flash point: | Undetermined. e: >190 °C >132 °C | |
| Flammability (solid, gas): | Not applicable. | |
| Ignition temperature: | Not determined. | |
| Decomposition temperature: Auto-ignition temperature: Explosive properties: | Not determined. Not determined. Product does not present an explosion hazard. | |
| EXPLOSION LIMITS Lower: Upper: | Not determined. Not determined. | |
| Vapour pressure: Density at 20 °C: Vapour density: Evaporation rate: | Not determined. 1.1 g/cm ³ Not determined. Not determined. | |
| Solubility in/Miscibility with:- Water: | Not miscible or difficult to mix. | |
| Partition coefficient: n-octanol/water: | Not determined. | |
| VISCOSITY at 25 °C Dynamic: Kinematic: Molecular weight | 700 ± 300 cps Not determined. Not determined. Not determined. | |
| Other information: | No further relevant information available. | |

(Contd. on page 6)

Revision Date: 19.10.2022

(Contd. of page 4)

Trade name: Silcor 780 HI-LP (Isocyanate)

10 Stability and Reactivity

Reactivity:

Stable under normal conditions. No further relevant information available.

Chemical stability:

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

Possibility of hazardous reactions

May vent and release flammable gas at high temperature. May explode when exposed to high temperature or heated.

Conditions to avoid:

Avoid contact with incompatible materials and condition. Avoid accumulation of electrostatic charges, Heating, Flames and hot surfaces. Avoid heat, sparks, open flames and other ignition sources.

Incompatible materials: Flammable materials, Reducing agents.

Hazardous decomposition products:

Carbon monoxide and carbon dioxide May emit flammable vapour, fume, hazardous gas if involved in fire.

11 Toxicological Information

Information on toxicological effects:

ACUTE TOXICITY

LD/LC50 values relevant for classification:

| 101-68-8 Diphenylmethane-4,4'-di-isocyanate | | | |
|---|----------|-----------------------|--|
| | LD50 | >10,000 mg/kg (rat) | |
| | LD50 | >9,400 mg/kg (rabbit) | |
| Inhalative | LC50, 4h | 0.368 mg/l (rat) | |
| | LC50, 1h | >2.24 mg/l (rat) | |

Primary irritant effect

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/irritation Causes serious eye irritation.

Inhalation:

Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation.

Ingestion: May cause damage to organs through prolonged or repeated exposure.

Respiratory or skin sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Sensitisation possible through skin contact.

Additional toxicological information: Suspected of causing cancer.

Other information :

The product was classified according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version.

12 Ecological Information

Toxicity:

AQUATIC TOXICITY No further relevant information available.

Persistence and degradability: No further relevant information available.

(Contd. of page 5)

Revision Date: 19.10.2022

Safety Data Sheet according to WHS Regulations

Printing Date: 01.12.2022

Version Number: 1.0

Trade name: Silcor 780 HI-LP (Isocyanate)

BEHAVIOUR IN ENVIRONMENTAL SYSTEMS

Bioaccumulative potential: No further relevant information available.

Mobility in soil: No further relevant information available.

ADDITIONAL ECOLOGICAL INFORMATION

General notes: Not known to be hazardous to water.

Results of PBT and vPvB assessment:

PBT: Not applicable. vPvB: Not applicable.

Other adverse effects: No further relevant information available.

13 Disposal considerations

Waste treatment methods:

Recommendation:

Refer to State Land Waste Authority for disposal considerations.



Must not be disposed together with household garbage. Do not allow product to reach sewage system.

UNCLEANED PACKAGING

Recommendation: Disposal must be made according to official regulations.

| 14 Transport information | | | |
|---|------------------------|--|--|
| UN-Number ADG, IMDG, IATA | Not Regulated | | |
| UN proper shipping name ADG, IMDG, IATA | Not Regulated | | |
| Transport hazard class(es) | | | |
| ADG, ADN, IMDG, IATA Class | Not Regulated | | |
| Packing group ADG, IMDG, IATA | Not Regulated | | |
| Environmental hazards: | Not applicable. | | |
| Special precautions for user: | Not applicable. | | |
| Transport in bulk according to Annex I MARPOL73/78 and the IBC Code: | II of Not Regulated | | |
| UN "Model Regulation": | Not Regulated | | |

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture:

See Section 2 for hazard identification.

Australia: Priority Existing Chemicals

None of the ingredients is listed.

(Contd. on page 8)

(Contd. of page 6)

Revision Date: 19.10.2022

Version Number: 1.0

Trade name: Silcor 780 HI-LP (Isocyanate)

Revision Date: 19.10.2022

(Contd. of page 7)

National regulations:

Other regulations, limitations and prohibitive regulations: All ingredients are listed on AICS.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases:

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H372 Causes damage to organs through prolonged or repeated exposure.

Department issuing SDS:

EHS Department, Asia Pacific Region SCIP, Canlubang, Calamba City, Laguna Philippines 4028 Tel: +63 (02) 8236-6820 to 24

Contact:

The first date of preparation: 04.12.2020

Number of revision times and the latest revision date: 1.0 / 19.10.2022

Sources: Raw material suppliers' safety data sheets were used as key data sources in the preparation of this safety data sheet.