



Printing Date: 01.12.2022 Version Number: 1.0 Revision Date: 19.10.2022

## 1 Identification

#### **Product identifier:**

Trade name: Silcor 780 HI-LP (Polyol)

Relevant identified uses of the substance or mixture, and uses advised against:

Relevant identified uses of the substance or mixture: Waterproofing.

Identified uses advised against: No further relevant information available.

## Details of the supplier of the safety data sheet:

## Manufacturer/supplier:

GCP Australia Pty. Ltd. 14 Colebard Street West Archerfield, Queensland 4108 Australia

#### Further information obtainable from:

Tel: 1800 334 444 Fax: +61 7-3275-7801 APMSDS@gcpat.com

Emergency telephone number: After hours - Tel. No. 1800 039 008

#### 2 Hazard(s) Identification

#### Classification of the substance or mixture:

Acute Tox. 5 H313 May be harmful in contact with skin.

Eye Irritation 2A H319 Causes serious eye irritation.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

#### **Label elements:**

GHS label elements The product is classified and labelled according to the Globally Harmonized System (GHS).

#### Hazard pictograms





GHS07

GHS08

### Signal word Warning

#### Hazard-determining components of labelling:

Diethylmethylbenzenediamine

#### **Hazard statements**

May be harmful in contact with skin.

Causes serious eye irritation.

May cause damage to organs through prolonged or repeated exposure.

#### **Precautionary statements**

Do not breathe dust/fume/gas/mist/vapours/spray.

Wash thoroughly after handling.

Wear eye protection / face protection.

IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Get medical advice/attention if you feel unwell.

If eye irritation persists: Get medical advice/attention.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

**Printing Date: 01.12.2022** Version Number: 1.0 **Revision Date: 19.10.2022** 

Trade name: Silcor 780 HI-LP (Polvol)

(Contd. of page 1)

#### Other hazards:

#### Results of PBT and vPvB assessment:

PBT: Not applicable. vPvB: Not applicable.

## 3 Composition and Information on Ingredients

#### **Chemical characterization: Mixture:**

**Description:** Mixture of substances listed below with non-hazardous additions.

Dangerous components:			
68479-98-	1 Diethylmethylbenzenediamine	STOT RE 2, H373	10-<20%
		Acute Tox. 4, H302; Acute Tox. 4, H312; Eye Irritation 2A, H319	
13463-67-	7 Titanium dioxide	Carc. 2, H351	1-<3%

#### Additional information:

Ingredients determined not to be hazardous are present in concentrations that do not exceed the relevant cut-off concentrations as found from NOHSC publication 'List of Designated Hazardous Substances' or have been found NOT to meet the criteria of a hazardous substance as defined in the NOHSC publication 'Approved Criteria for Classifying Hazardous Substances'.

## **4 First Aid Measures**

## **Description of first aid measures:**

General information: Get medical advice/attention if you feel unwell.

After inhalation: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

After skin contact: Wash with plenty of soap and water.

After eye contact: Rinse cautiously with water for several minutes.

After swallowing:

Rinse mouth.

Do NOT induce vomiting.

Call for a doctor immediately.

**Information for doctor:** 

Most important symptoms and effects, both acute and delayed: Irritating to eyes.

**Indication of any immediate medical attention and special treatment needed:** No further relevant information available.

## 5 Fire Fighting Measures

**Suitable extinguishing agents:** CO2, powder or water spray. Fight larger fires with water spray.

## Special hazards arising from the substance or mixture:

During heating or in case of fire poisonous gases are produced.

#### **Advice for firefighters:**

Protective equipment: Wear self-contained respiratory protective device.

Additional information: Collect contaminated fire fighting water separately. It must not enter the sewage system.

#### **6 Accidental Release Measures**

## Personal precautions, protective equipment and emergency procedures:

Ensure adequate ventilation.

(Contd. on page 3)

Printing Date: 01.12.2022 Version Number: 1.0 Revision Date: 19.10.2022

Trade name: Silcor 780 HI-LP (Polyol)

(Contd. of page 2)

Wear protective equipment. Keep unprotected persons away.

Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system.

Methods and material for containment and cleaning up: Send for recovery or disposal in suitable receptacles.

#### Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## 7 Handling and Storage

## **HANDLING**

#### Precautions for safe handling:

Prevent formation of aerosols.

Do not eat, drink or smoke when using this product.

Store in a well-ventilated place. Keep container tightly closed.

Keep only in original container.

Use only outdoors or in a well-ventilated area.

Information about fire - and explosion protection: No special measures required.

## Conditions for safe storage, including any incompatibilities:

#### **STORAGE**

Information about storage in one common storage facility: Keep respiratory protective device available.

#### Further information about storage conditions:

Keep container tightly sealed.

Protect from frost.

Store in a dry place.

Keep cool.

**Specific end use(s):** No further relevant information available.

## 8 Exposure controls and personal protection

Additional information about design of technical facilities: No further data; see item 7.

#### Control parameters:

Control parameters.			
Ingredients with lim	Ingredients with limit values that require monitoring at the workplace:		
13463-67-7 Titaniur	13463-67-7 Titanium dioxide		
WES (Australia)	Long-term value: 10 mg/m <sup>3</sup>		
WEL (Great Britain)	Long-term value: 10* 4** mg/m³ *total inhalable **respirable		
PEL (USA)	Long-term value: 15* mg/m³ *total dust		
REL (USA)	See Pocket Guide App. A		
TLV (USA)	Long-term value: 10 mg/m <sup>3</sup>		

Additional information: Based on the lists valid at the date of SDS creation.

(Contd. on page 4)

Printing Date: 01.12.2022 Version Number: 1.0 Revision Date: 19.10.2022

Trade name: Silcor 780 HI-LP (Polyol)

(Contd. of page 3)

## **Exposure controls:**

## PERSONAL PROTECTIVE EQUIPMENT

#### General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

#### **Respiratory protection:**

Control exposure to ingredients with workplace control parameters if mentioned above. If no ingredients are listed, respiratory protection is generally not required.

If exposure limits are listed and may be exceeded, use approved respiratory protective equipment and filter type appropriate for the listed ingredients. (NIOSH, CEN, etc.).

Protection of hands: Protective gloves.

Material of gloves: Rubber gloves.

Penetration time of glove material:

The exact breakthrough time has to be determined by the manufacturer of the protective gloves and has to be observed.

#### **Eye protection:**



Safety glasses with side shield protection.

#### **Body protection:**

Use personal protective equipment as required.

Take off contaminated clothing and wash before reuse.

$\mathbf{o}$	• 1			• 1 To		4 ·
uPh	VCICO	and	( ham	ICOL P	ronar	TAC
	v sicai	anu	Chem	icai i	IODCI	$\mathbf{u}\mathbf{c}\mathbf{s}$

Information on basic physical and chemical properties:		
GENERAL INFORMATION Appearance: Form: Colour: Odour: Odour threshold:	Liquid. Coloured Slight Musty Not determined.	
pH-value (~):  Change in conditions:- Melting point/freezing point: Initial boiling point and boiling range: Flash point:	Undetermined.	
Flammability (solid, gas):	Not applicable.	
Ignition temperature:	Not determined.	
Decomposition temperature: Auto-ignition temperature: Explosive properties:	Not determined. Not determined. Product does not present an explosion hazard.	
EXPLOSION LIMITS Lower: Upper:	Not determined. Not determined.	
Vapour pressure: Density at 20 °C: Vapour density: Evaporation rate:	Not determined. 1 g/cm³ Not determined. Not determined.	
Solubility in/Miscibility with:- Water:	Not miscible or difficult to mix.	

(Contd. on page 5)

**Printing Date: 01.12.2022** Version Number: 1.0 **Revision Date: 19.10.2022** 

Trade name: Silcor 780 HI-LP (Polyol)

	(C	Contd. of page 4)
Partition coefficient: n-octanol/water:	Not determined.	
VISCOSITY at 25 °C Dynamic: Kinematic:	600 ± 300 cps Not determined. Not determined.	
Molecular weight	Not determined. Not determined.	
Other information:	No further relevant information available.	

## 10 Stability and Reactivity

## **Reactivity:**

Stable under normal conditions.

No further relevant information available.

### **Chemical stability:**

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

#### Possibility of hazardous reactions

May vent and release flammable gas at high temperature.

May explode when exposed to high temperature or heated.

#### **Conditions to avoid:**

Avoid contact with incompatible materials and condition.

Avoid accumulation of electrostatic charges, Heating, Flames and hot surfaces.

Avoid heat, sparks, open flames and other ignition sources.

**Incompatible materials:** Flammable materials, Reducing agents.

### **Hazardous decomposition products:**

Carbon monoxide and carbon dioxide

May emit flammable vapour, fume, hazardous gas if involved in fire.

## 11 Toxicological Information

## **Information on toxicological effects:**

#### ACUTE TOXICITY

A	ACUTE TOXICITY		
L	LD/LC50 values relevant for classification:		
68	68479-98-1 Diethylmethylbenzenediamine		
О	Oral LD50 738 mg/kg (rat) (OECD Test Guideline 401)		
D	ermal	LD50	738 mg/kg (rat)
		LC50, 48h 0.5 mg/l (daphnia magna)	
			1.94 mg/l (fish)
13	13463-67-7 Titanium dioxide		
О	ral	LD50	>5,000 mg/kg (rat)

#### Primary irritant effect

Skin corrosion/irritation No irritating effect.

Serious eye damage/irritation Causes serious eye irritation.

**Ingestion:** May cause damage to organs through prolonged or repeated exposure.

## Other information:

The product was classified according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version.

Printing Date: 01.12.2022 Version Number: 1.0 Revision Date: 19.10.2022

Trade name: Silcor 780 HI-LP (Polvol)

(Contd. of page 5)

## 12 Ecological Information

## **Toxicity:**

AQUATIC TOXICITY No further relevant information available.

Persistence and degradability: No further relevant information available.

#### BEHAVIOUR IN ENVIRONMENTAL SYSTEMS

Bioaccumulative potential: No further relevant information available.

Mobility in soil: No further relevant information available.

#### **ECOTOXICAL EFFECTS**

Remark: Toxic for fish

### ADDITIONAL ECOLOGICAL INFORMATION

#### **General notes:**

Toxic for aquatic organisms.

Also poisonous for fish and plankton in water bodies.

#### Results of PBT and vPvB assessment:

**PBT:** Not applicable. **vPvB:** Not applicable.

Other adverse effects: No further relevant information available.

## 13 Disposal considerations

### Waste treatment methods:

#### **Recommendation:**

Refer to State Land Waste Authority for disposal considerations.



Must not be disposed together with household garbage. Do not allow product to reach sewage system.

## UNCLEANED PACKAGING

Recommendation: Disposal must be made according to official regulations.

## 14 Transport information

UN-Number ADG, IMDG, IATA	UN3082
UN proper shipping name ADG, IATA	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Diethylmethylbenzenediamine)
IMDG	ENVIRÒNMÉNTALLY HAZARDOÚS SUBSTANCE, LIQUID, N.O.S. (Diethylmethylbenzenediamine), MARINE POLLUTANT

## Transport hazard class(es)

ADG, IMDG, IATA



Class 9 Miscellaneous dangerous substances and articles.

Label 9

(Contd. on page 7)

Printing Date: 01.12.2022 Version Number: 1.0 Revision Date: 19.10.2022

Trade name: Silcor 780 HI-LP (Polyol)

	(Contd. of page 6)
Packing group ADG, IMDG, IATA	III
Environmental hazards:  Marine pollutant: Special marking (ADG): Special marking (IATA):	Product contains environmentally hazardous substances: Diethylmethylbenzenediamine Symbol (fish and tree) Symbol (fish and tree) Symbol (fish and tree)
Special precautions for user: Hazard identification number (Kemler code): EMS Number: Stowage Category	Warning: Miscellaneous dangerous substances and articles. 90 F-A,S-F A
Transport in bulk according to Annex II o MARPOL73/78 and the IBC Code:	Not Regulated
Transport/Additional information:	
ADG Limited quantities (LQ) Excepted quantities (EQ)  Transport category	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml 3
Tunnel restriction code Remarks:	(-) ≤5L, ADR Special Provision 375.
IMDG Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml
Remarks: IATA Remarks:	Maximum net quantity per outer packaging: 1000 ml ≤5L, IMDG 2.10.2.7 ≤5L, IATA Special Provision 197.
UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (DIETHYLMETHYLBENZENEDIAMINE), 9, III

## 15 Regulatory information

## Safety, health and environmental regulations/legislation specific for the substance or mixture:

See Section 2 for hazard identification.

**Australia: Priority Existing Chemicals** 

None of the ingredients is listed.

National regulations:

Other regulations, limitations and prohibitive regulations: All ingredients are listed on AICS.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**Relevant phrases:** 

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H319 Causes serious eye irritation.

H351 Suspected of causing cancer.

(Contd. on page 8)

Printing Date: 01.12.2022 Version Number: 1.0 Revision Date: 19.10.2022

Trade name: Silcor 780 HI-LP (Polyol)

H373 May cause damage to organs through prolonged or repeated exposure.

(Contd. of page 7)

## **Department issuing SDS:**

EHS Department, Asia Pacific Region SCIP, Canlubang, Calamba City, Laguna Philippines 4028

Tel: +63 (02) 8236-6820 to 24

#### **Contact:**

The first date of preparation: 22.12.2020

Number of revision times and the latest revision date:  $1.0 \, / \, 19.10.2022$ 

Sources: Raw material suppliers' safety data sheets were used as key data sources in the preparation of this safety data sheet.

A T T