

Safety Data Sheet

according to WHS Regulations

Printing Date: 01.12.2022

Version Number: 1.0

Revision Date: 01.12.2022

# 1 Identification

### **Product identifier:**

Trade name: Metaset Structural Adhesive

Relevant identified uses of the substance or mixture, and uses advised against:

Relevant identified uses of the substance or mixture: Waterproofing.

Identified uses advised against: No further relevant information available.

#### Details of the supplier of the safety data sheet:

Manufacturer/supplier:

GCP Australia Pty. Ltd. 14 Colebard Street West Archerfield, Queensland 4108 Australia

# Further information obtainable from:

email: msds.gcp@gcpat.com Tel: 1800 334 444

Fax: +61 7-3275-7801

APMSDS@gcpat.com

Emergency telephone number: After hours - Tel. No. 1800 039 008

## 2 Hazard(s) Identification

#### **Classification of the substance or mixture:**

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irritation 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

#### Label elements:

GHS label elements The product is classified and labelled according to the Globally Harmonized System (GHS).

#### Hazard pictograms



Signal word Danger

Hazard-determining components of labelling:

Methyl methacrylate n-butyl methacrylate

#### Hazard statements

Highly flammable liquid and vapour. Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. May cause respiratory irritation. **Precautionary statements** Keep away from heat/sparks/open flames/hot surfaces. No smoking. Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting equipment.

Version Number: 1.0

Revision Date: 01.12.2022

# Trade name: Metaset Structural Adhesive

(Contd. of page 1)			
Use only non-sparking tools. Take precautionary measures against static discharge.			
Avoid breathing dust/fume/gas/mist/vapours/spray.			
Wash thoroughly after handling.			
Use only outdoors or in a well-ventilated area.			
Contaminated work clothing should not be allowed out of the workplace.			
Wear protective gloves/protective clothing/eye protection/face protection. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.			
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.			
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue			
rinsing.			
Call a POISON CENTER/doctor if you feel unwell. If skin irritation or rash occurs: Get medical advice/attention.			
If eye irritation persists: Get medical advice/attention.			
Take off contaminated clothing and wash it before reuse.			
In case of fire: Use CO2, powder or water spray to extinguish.			
Store in a well-ventilated place. Keep container tightly closed.			
Store in a well-ventilated place. Keep cool.			
Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations.			
Hazard description: Flammable			
Other hazards:			
Results of PBT and vPvB assessment:			
PBT: Not applicable.			
vPvB: Not applicable.			
<b>3</b> Composition and Information on Ingredients			

# Chemical characterization: Mixture:

**Description:** Mixture of substances listed below with non-hazardous additions.

Dangerous components:				
80-62-6	Methyl methacrylate	30-<50%		
	Flam. Liq. 2, H225 Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335			
97-88-1	n-butyl methacrylate	10-<20%		
	Flam. Liq. 3, H226 Skin Irrit. 2, H315; Eye Irritation 2A, H319; Skin Sens. 1, H317; STOT SE 3, H335			
	N,N-dimethyl-p-toluidine	0.1-<1%		
	Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331 Carc. 2, H351; STOT RE 2, H373			
	Flam. Liq. 4, H227			

### Additional information:

Ingredients determined not to be hazardous are present in concentrations that do not exceed the relevant cut-off concentrations as found from NOHSC publication 'List of Designated Hazardous Substances' or have been found NOT to meet the criteria of a hazardous substance as defined in the NOHSC publication 'Approved Criteria for Classifying Hazardous Substances'.

# **4 First Aid Measures**

#### **Description of first aid measures:**

General information: Get medical advice/attention if you feel unwell.

After inhalation: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

After skin contact: Wash with plenty of soap and water.

After eye contact: Rinse cautiously with water for several minutes.

After swallowing:

Rinse mouth.

(Contd. on page 3)

### Safety Data Sheet according to WHS Regulations

Printing Date: 01.12.2022

Version Number: 1.0

Revision Date: 01.12.2022

# Trade name: Metaset Structural Adhesive

(Contd. of page 2)

Do NOT induce vomiting.

Information for doctor:

Most important symptoms and effects, both acute and delayed:

May cause sensitisation by skin contact.

Irritating to eyes.

Indication of any immediate medical attention and special treatment needed: No further relevant information available.

# **5** Fire Fighting Measures

# Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fire with alcohol resistant foam.

For safety reasons unsuitable extinguishing agents: Water jet.

Special hazards arising from the substance or mixture: No further relevant information available.

Advice for firefighters:

Protective equipment: Wear self-contained respiratory protective device.

Additional information: Collect contaminated fire fighting water separately. It must not enter the sewage system.

# **6** Accidental Release Measures

# Personal precautions, protective equipment and emergency procedures:

Ensure adequate ventilation.

Wear protective equipment. Keep unprotected persons away.

Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system.

Methods and material for containment and cleaning up: Send for recovery or disposal in suitable receptacles.

**Reference to other sections** 

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

# 7 Handling and Storage

# HANDLING

### Precautions for safe handling:

Prevent formation of aerosols.

Flammable mixtures with air can be formed in emptied containers. Do not puncture, cut, drill, heat or weld uncleaned drums.

Do not eat, drink or smoke when using this product.

Store in a well-ventilated place. Keep container tightly closed.

Keep only in original container.

Use only outdoors or in a well-ventilated area.

Information about fire - and explosion protection:



Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Version Number: 1.0

Trade name: *Metaset Structural Adhesive* 

Use explosion-proof apparatus / fittings and spark-proof tools.

Empty containers may retain hazardous residue, both liquid and vapour. Do not cut, drill, grind or weld on or near container, whether empty or full.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Ground/bond container and receiving equipment.

# Conditions for safe storage, including any incompatibilities:

#### STORAGE

Requirements to be met by storerooms and receptacles: Store in a cool location.

#### Further information about storage conditions:

Keep container tightly sealed.

Protect from frost.

Store in a dry place.

Keep cool.

Specific end use(s): No further relevant information available.

# 8 Exposure controls and personal protection

### Additional information about design of technical facilities: No further data; see item 7.

Control parameters:				
Ingredients with limit values that require monitoring at the workplace:				
80-62-6 Methyl methacrylate				
WES (Australia)	Short-term value: 416 mg/m <sup>3</sup> , 100 ppm Long-term value: 208 mg/m <sup>3</sup> , 50 ppm Sen			
WEL (Great Britain)	Short-term value: 416 mg/m <sup>3</sup> , 100 ppm Long-term value: 208 mg/m <sup>3</sup> , 50 ppm			
PEL (USA)	Long-term value: 410 mg/m <sup>3</sup> , 100 ppm			
REL (USA)	Long-term value: 410 mg/m <sup>3</sup> , 100 ppm			
TLV (USA)	Short-term value: 100 ppm Long-term value: 50 ppm DSEN, A4			
99-97-8 N,N-dimeth	99-97-8 N,N-dimethyl-p-toluidine			
WEEL (USA)	Long-term value: 0.5 ppm			

Additional information: Based on the lists valid at the date of SDS creation.

### **Exposure controls:**

#### PERSONAL PROTECTIVE EQUIPMENT

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

**Respiratory protection:** 

Control exposure to ingredients with workplace control parameters if mentioned above. If no ingredients are listed, respiratory protection is generally not required.

If exposure limits are listed and may be exceeded, use approved respiratory protective equipment and filter type appropriate for the listed ingredients. (NIOSH, CEN, etc.).

Protection of hands: Protective gloves.

Material of gloves: Rubber gloves.

#### Penetration time of glove material:

The exact breakthrough time has to be determined by the manufacturer of the protective gloves and has to be observed.

(Contd. of page 3)

Revision Date: 01.12.2022

Version Number: 1.0

# Trade name: Metaset Structural Adhesive

#### Eye protection:



Safety glasses with side shield protection.

### **Body protection:**

Use personal protective equipment as required.

Take off contaminated clothing and wash before reuse.

# **9** Physical and Chemical Properties

Information on hasis abusical on					
i v	Information on basic physical and chemical properties:				
GENERAL INFORMATION Appearance:					
Form:	Viscous liquid.				
Colour: Odour:	Various. Characteristic.				
Odour: Odour threshold:	Not determined.				
pH-value (~):	Not determined.				
Change in conditions:- Melting point/freezing point: Initial boiling point and boiling range Flash point:	Undetermined. ~100 °C ~17 °C				
Flammability (solid, gas):	Highly flammable.				
Ignition temperature:	~430 °C				
Decomposition temperature: Auto-ignition temperature: Explosive properties:	Not determined. Not determined. In use, may form flammable/explosive vapour-air mixture.				
EXPLOSION LIMITS Lower: Upper:	2 Vol % 13 Vol %				
Vapour pressure:	Not determined.				
Density at 20 °C:	$\sim 1-1.3 \text{ g/cm}^3$				
Vapour density:	Not determined. Not determined.				
Evaporation rate:	Not determined.				
Solubility in/Miscibility with:- Water:	Not miscible or difficult to mix.				
Partition coefficient: n-octanol/water:	Not determined.				
VISCOSITY Dynamic at 20 °C:	90-250 mPas				
Kinematic:	Not determined.				
SOLVENT CONTENT					
VOC (EC):	6.79 %				
Molecular weight	Not determined.				
Other information:	No further relevant information available.				

# **10 Stability and Reactivity**

Reactivity: Will exothermically polymerise in the presence of initiators.

Chemical stability: Stable in the presence of inhibitor.

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

(Contd. on page 6)

Revision Date: 01.12.2022

(Contd. of page 4)

Version Number: 1.0

Trade name: Metaset Structural Adhesive

# Possibility of hazardous reactions

Susceptible to polymerisation initiated by prolonged storage or the presence of catalyst.

Conditions to avoid: Keep away from heat/sparks/open flames/hot surfaces. No smoking.

# **Incompatible materials:**

Polymerisation catalysts, such as peroxy or azo compounds, strong acids, alkalis and oxidising agents. Oxides and salts of transition metals. Organic Nitrogen containing compounds. Cyclohexanone/Cyclohexenol tautomer.

Hazardous decomposition products: Carbon monoxide and carbon dioxide

### **11 Toxicological Information**

#### Information on toxicological effects:

#### ACUTE TOXICITY

97-88-1 n-butyl methacrylate					
Dermal	LD50	22,600 mg/kg (rat)			
	LD50	11,300 mg/kg (rabbit)			

Inhalative LC50, 4h 4,910 mg/l (rat)

Primary irritant effect

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/irritation Causes serious eye irritation.

Inhalation: May cause respiratory irritation.

Respiratory or skin sensitisation Sensitisation possible through skin contact.

#### **Other information :**

The product was classified according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version.

### **12 Ecological Information**

#### **Toxicity:**

AQUATIC TOXICITY No further relevant information available.

Persistence and degradability: No further relevant information available.

### **BEHAVIOUR IN ENVIRONMENTAL SYSTEMS**

Bioaccumulative potential: No further relevant information available.

Mobility in soil: No further relevant information available.

### ADDITIONAL ECOLOGICAL INFORMATION

General notes: Not known to be hazardous to water.

#### **Results of PBT and vPvB assessment:**

**PBT:** Not applicable. **vPvB:** Not applicable.

Other adverse effects: No further relevant information available.

(Contd. on page 7)

ATT

(Contd. of page 5)

Version Number: 1.0

Trade name: Metaset Structural Adhesive

# **13 Disposal considerations**

### Waste treatment methods:

### **Recommendation:**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Refer to State Land Waste Authority for disposal considerations.

# **UNCLEANED PACKAGING**

Recommendation: Disposal must be made according to official regulations.

14 Transport information		
UN-Number ADG, IMDG, IATA	UN1866	
UN proper shipping name ADG, IMDG, IATA	RESIN SOLUTION	
Transport hazard class(es)		
ADG, IMDG, IATA		
Class Label	3 Flammable liquids. 3	
Packing group ADG, IMDG, IATA	П	
Environmental hazards:	Not applicable.	
Special precautions for user: Hazard identification number (Kemler code): EMS Number: Stowage Category	Warning: Flammable liquids. 33 F-E, <u>S-E</u> B	
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: Not Regulated		
Transport/Additional information:		
ADG Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml	
Transport category Tunnel restriction code	2 D/E	
IMDG Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml	

(Contd. on page 8)

(Contd. of page 6)

Version Number: 1.0

Trade name: Metaset Structural Adhesive

**15 Regulatory information** 

Safety, health and environmental regulations/legislation specific for the substance or mixture:

See Section 2 for hazard identification.

Australia: Priority Existing Chemicals

None of the ingredients is listed.

National regulations:

Other regulations, limitations and prohibitive regulations: All ingredients are listed on AICS.

Registered in the international inventory lists: AICS (Australia)

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

# **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

### **Relevant phrases:**

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H227 Combustible liquid.
- H301 Toxic if swallowed.
- H311 Toxic in contact with skin. H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H331 Toxic if inhaled.
- H335 May cause respiratory irritation.
- H351 Suspected of causing cancer.
- H373 May cause damage to organs through prolonged or repeated exposure.

### **Department issuing SDS:**

EHS Department, Asia Pacific Region SCIP, Canlubang, Calamba City, Laguna Philippines 4028 Tel: +63 (02) 8236-6820 to 24

### **Contact:**

The first date of preparation: 01.03.2021 Number of revision times and the latest revision date: 1.0 / 01.12.2022 (Contd. of page 7)

Revision Date: 01.12.2022