

PREPRUFE® CJ Tape

Product Description

PREPRUFE® CJ Tape is a specially formulated, double-sided, reinforced, pressure-sensitive tape. The bottom side of the tape has a highly aggressive, pressure-sensitive adhesive which is designed to adhere to penetrations, protrusions, PREPRUFE® and BITUTHENE® membranes. The top side has another layer of adhesive and a protective coating.

A thin, flexible film is sandwiched between the two layers of pressure-sensitive adhesive. The tape develops a continuous mechanical bond with the concrete that is cast against it.

PREPRUFE® CJ Tape is supplied in rolls and is interwound with a silicone coated release liner.

Use

PREPRUFE® CJ Tape is used at construction joints in concrete that is cast against it. It is also used to patch damaged areas in the PREPRUFE® membranes or in critical areas where a wider tape is required.

The tape is a critical component of the PREPRUFE® system since it is designed to develop a continuous mechanical bond to concrete that is cast against it.

Supply

PREPRUFE CJ TAPE LT* OR HC*	
Thickness (nominal)*	0.7mm
Roll Size	200mm x 15.0m
Roll Weight	4kg
Minimum Edge / End Laps	75mm

^{*}LT denotes ambient temperature between -4°C and $+30^{\circ}\text{C}$

Application

Apply PREPRUFE® CJ Tape when ambient temperatures are -4 °C or above. Select correct LT or HT grade for the application temperature experienced. Wipe PREPRUFE® membranes clean to remove any dirt, dust or moisture. Clean the surface of penetrations or protrusions with a wire brush to remove dirt, dust, rust and loose particles.

Unroll the tape and adhere the exposed pressure-sensitive adhesive surface to the membrane or penetration. The protective coating surface of the tape should face toward the concrete to be cast.

^{*}HC denotes application temperature between $+10^{\circ}$ C and $+40^{\circ}$ C

^{*}Nominal thickness refers to the thickness of the tape without release liner.



Use heavy hand pressure or a hand roller to maximise adhesion. Remove the release liner during application. Cast concrete or apply shotcrete within 30 days of application of the tape.

gcpat.com.au | Customer Service AU: 1800 334 444 - NZ: 0800 552 235 | anzorders@gcpat.com

We hope the information here will be helpful. It is based on data and knowledge considered to be true and accurate, and is offered for consideration, investigation and verification by the user, but we do not warrant the results to be obtained. Please read all statements, recommendations, and suggestions in conjunction with our conditions of sale, which apply to all goods supplied by us. No statement, recommendation, or suggestion is intended for any use that would infringe any patent, copyright, or other third party right.

BITUTHENE® and PREPRUFE® are trademarks, which may be registered in the United States and/or other countries, of GCP Applied Technologies, Inc. This trademark list has been compiled using available published information as of the publication date and may not accurately reflect current trademark ownership or status.

© Copyright 2025 GCP Applied Technologies, Inc. All rights reserved.

GCP Applied Technologies Inc., 2325 Lakeview Parkway, Alpharetta, GA 30009, USA

GCP Australia Pty. Ltd., 14 Colebard Street West, Archerfield, Brisbane, Queensland 4108, Australia

This document is only current as of the last updated date stated below and is valid only for use in Australia. It is important that you always refer to the currently available information at the URL below to provide the most current product information at the time of use. Additional literature such as Contractor Manuals, Technical Bulletins, Detail Drawings and detailing recommendations and other relevant documents are also available on www.gcpat.com.au. Information found on other websites must not be relied upon, as they may not be up-to-date or applicable to the conditions in your location and we do not accept any responsibility for their content. If there are any conflicts or if you need more information, please contact GCP Customer Service.

_ast Updated: 2025-06-2!